

HYDROSTATIC VIBRATORY ROLLER

SPECIFICATIONS:

18HP Honda
Electric Start
Hydrostatic Transmission
Speed: 4.7mph/
Fuel Capacity: 6.3 Gal.
Fuel Consumption: 1.2gph
40 Gallon Water Tank
3000lb. Centrifugal Force
3900 VPM
9.2 Ft. Outside Turn Rad.
27% Gradability
Weight: 2400 lbs
Dimen: 82" x 41" x 60"



PROCEDURE:

- Unit will be sent out with water tanks empty.
- Customer will be instructed on forward, reverse and neutral positions.
- Caution must be taken when loading and unloading (if drums start spinning, lower the elevation of the ramps).
- Unit makes an ideal lawn roller. Due to narrow base warn the customer of use on sides of grades.
- Unit is ideal for confined area when asphaltting or preparation for concrete.
- Water tank on machine to provide lubrication if needed.
- Grab hooks located front and rear of machine to raise and lower machine if ramp unavailable.
- Check engine oil and air filter each time the tank is refilled with fuel.
- Every 8 hours check all nuts and bolts for tightness
- Shutdown: Allow the engine to idle down approximately 5 minutes to reduce engine heat from burning protective coating of oil from the cylinder wall.
- Customer will be charged for any cleanup and or damage due to neglect.