



SNOWMOBILES
SERVICE
Bulletin



September 21, 2010 Subject: **High Altitude / Sea Level Specifications**

No. **2011-6**

REVISION ►1◀
►October 28,
2010◀

►UNDERLINE TEXT(S) BETWEEN ARROWS IS (ARE) ADDED ELEMENT(S) TO THE PREVIOUS PUBLICATION.◀

YEAR	MODEL	MODEL NUMBER	SERIAL NUMBER
2011	All	All	All

TABLE OF CONTENTS

	Page		Page
GENERAL INFORMATION	4	Main Jet Chart	13
Previous Model Year Vehicles	4	Additional Information	13
Reverse Connector	4	SKANDIC WT 550F (YETI II)	14
GRAND TOURING SPORT 550F (CAN/US AND EUROPE) / RENEGADE™ SPORT 550F (CAN/US AND EUROPE)	5	Drive Pulley	14
Drive Pulley	5	Driven Pulley	14
Driven Pulley	5	Carburetion (Refer to appropriate Specification Booklet for part numbers)	15
Carburetion (Refer to appropriate Specification Booklet for part numbers)	6	Main Jet Chart	15
Main Jet Chart	7	GRAND TOURING SPORT 600	16
Additional Information	7	Drive Pulley	16
MX Z™ SPORT 550F / MX Z TNT™ 550F (CAN/US AND EUROPE)	8	Driven Pulley	16
Drive Pulley	8	Carburetion (Refer to appropriate Specification Booklet for part numbers)	17
Driven Pulley	8	Main Jet Chart	17
Carburetion (Refer to appropriate Specification Booklet for part numbers)	9	MX Z SPORT 600 / MX Z TNT 600	18
Main Jet Chart	10	Drive Pulley	18
Additional Information	10	Driven Pulley	18
EXPEDITION® SPORT 550F / SKANDIC™ TUNDRA™ 550F / SKANDIC TUNDRA SPORT 550F / SKANDIC TUNDRA LT 550F (CAN/US AND EUROPE)	11	Carburetion (Refer to appropriate Specification Booklet for part numbers)	19
Drive Pulley	11	Main Jet Chart	19
Driven Pulley	11	SUMMIT™ SPORT 146" 600	20
Carburetion (Refer to appropriate Specification Booklet for part numbers)	12	Drive Pulley	20
		Driven Pulley	20
		Carburetion (Refer to appropriate Specification Booklet for part numbers)	21
		Main Jet Chart	21
		Vehicle Calibration	22

**EXPEDITION LE 600 H.O. E-TEC® /
EXPEDITION SE 600 H.O. E-TEC / SKANDIC
WT 600 H.O. E-TEC (REV-XU™) 23**

- Drive Pulley..... 23
- Driven Pulley 23

GSX™ LE 600 H.O. E-TEC®..... 24

- Drive Pulley..... 24
- Driven Pulley 24

GRAND TOURING LE 600 H.O. E-TEC.. 25

- Drive Pulley..... 25
- Driven Pulley 25

**MX Z TNT 600 H.O. E-TEC / MX Z™
X™ 600 H.O. E-TEC / MX Z X-RS™ 600
H.O. E-TEC (CAN/US AND EUROPE) /
RENEGADE ADRENALINE 600 H.O. E-TEC
(CAN/US AND EUROPE) / RENEGADE™
BACKCOUNTRY™ 600 H.O. E-TEC /
RENEGADE BACKCOUNTRY X 600
H.O. E-TEC (CAN/US AND EUROPE) /
RENEGADE X 600 H.O. E-TEC..... 26**

- Drive Pulley..... 26
- Driven Pulley 26

**SKANDIC TUNDRA Xtreme 600 H.O.
E-TEC (CAN/US AND EUROPE)..... 27**

- Drive Pulley..... 27
- Driven Pulley 27
- Vehicle Calibration 27

**SUMMIT EVEREST™ 146" 600 H.O. E-TEC
/ SUMMIT X 154" 600 H.O. E-TEC..... 28**

- Drive Pulley..... 28
- Driven Pulley 28
- Vehicle Calibration 28

**SUMMIT EVEREST 146" 600 H.O. E-TEC
(EUROPE) 29**

- Drive Pulley..... 29
- Driven Pulley 29
- Vehicle Calibration 29

MX Z TNT 800R POWER TEK..... 30

- Drive Pulley..... 30
- Driven Pulley 30
- Carburetion (Refer to appropriate Specification
Booklet for part numbers) 31
- Main Jet Chart 31

**RENEGADE ADRENALINE 800R POWER
TEK / RENEGADE SP 800R POWER
TEK 32**

- Drive Pulley..... 32
- Driven Pulley 32
- Carburetion (Refer to appropriate Specification
Booklet for part numbers) 33

- Main Jet Chart 33

**RENEGADE™ BACKCOUNTRY™ 800R
POWER TEK 34**

- Drive Pulley..... 34
- Driven Pulley 34
- Carburetion (Refer to appropriate Specification
Booklet for part numbers) 35
- Main Jet Chart 35

**SUMMIT EVEREST 146", 154" & 163" 800R
POWER TEK / SUMMIT SP 154" 800R
POWER TEK 36**

- Drive Pulley..... 36
- Driven Pulley 36
- Carburetion (Refer to appropriate Specification
Booklet for part numbers) 37
- Main Jet Chart 37
- Vehicle Calibration 38

**MX Z TNT 800R E-TEC / MX Z X 800R
E-TEC / MX Z X-RS 800R E-TEC (CAN/US
AND EUROPE) 39**

- Drive Pulley..... 39
- Driven Pulley 39

**RENEGADE ADRENALINE 800R E-TEC /
RENEGADE X 800R E-TEC 40**

- Drive Pulley..... 40
- Driven Pulley 40

**RENEGADE BACKCOUNTRY 800R E-TEC /
RENEGADE BACKCOUNTRY X 800R E-TEC
(CAN/US AND EUROPE) 41**

- Drive Pulley..... 41
- Driven Pulley 41

**SUMMIT EVEREST 154" 800R E-TEC /
SUMMIT FREERIDE™ 154" 800R E-TEC
/ SUMMIT X 146", 154" & 163" 800R
E-TEC..... 42**

- Drive Pulley..... 42
- Driven Pulley 42
- Vehicle Calibration 42

**SUMMIT FREERIDE 154" 800R E-TEC
(EUROPE) / SUMMIT X 146", 154" & 163"
800R E-TEC (EUROPE) 43**

- Drive Pulley..... 43
- Driven Pulley 43
- Vehicle Calibration 43

SKANDIC SWT V-800 (YETI II)..... 44

- Drive Pulley..... 44
- Driven Pulley 44

**EXPEDITION SPORT 600 ACE™ /
RENEGADE™ SPORT 600 ACE (CAN/US
AND EUROPE) / SKANDIC TUNDRA LT
600 ACE (CAN/US AND EUROPE)..... 45**

Drive Pulley..... 45

Driven Pulley 45

**GRAND TOURING SPORT 600 ACE / MX Z
SPORT 600 ACE..... 46**

Drive Pulley..... 46

Driven Pulley 46

**GRAND TOURING SPORT 600 ACE
(EUROPE) / MX Z TNT 600 ACE 47**

Drive Pulley..... 47

Driven Pulley 47

SKANDIC WT 600 ACE (REV-XU)..... 48

Drive Pulley..... 48

Driven Pulley 48

**EXPEDITION LE 1200 4-TEC® /
EXPEDITION SE 1200 4-TEC 49**

Drive Pulley..... 49

Driven Pulley 49

GSX LE 1200 4-TEC 50

Drive Pulley..... 50

Driven Pulley 50

**GRAND TOURING LE 1200 4-TEC / GRAND
TOURING SE 1200 4-TEC (CAN/US AND
EUROPE) / GSX SE 1200 4-TEC..... 51**

Drive Pulley..... 51

Driven Pulley 51

**MX Z TNT 1200 4-TEC / MX Z X 1200
4-TEC 52**

Drive Pulley..... 52

Driven Pulley 52

**RENEGADE ADRENALINE 1200 4-TEC /
RENEGADE X 1200 4-TEC (CAN/US AND
EUROPE) 53**

Drive Pulley..... 53

Driven Pulley 53

GENERAL INFORMATION

Previous Model Year Vehicles

This bulletin supplies all the information required to modify current year vehicles for high altitude and/or sea level riding.

MODEL YEAR	LATEST REVISION OF BULLETIN NO.
2010	2010-5
2009	2009-5
2008	2008-6
2007	2007-1
2006	2006-2
2005	2005-6
2004	2004-2
2003	2003-5
2002	2002-5
2001	2001-1 and 2001-2
2000	2000-1 and 2000-2

NOTE: Throughout this entire document, shaded areas give factory settings (that could apply through different altitudes) while N/A stands for "not applicable".


⚠ CAUTION The following modifications and adjustments apply for high altitude operation as well as sea level operation.

PARTS AND LABOR COST ARE NOT COVERED BY BRP LIMITED WARRANTY.

Reverse Connector

The reverse connector (P/N 515 174 700) is used at 1 800 m (6,000 ft) altitude and higher for all FAN cooled models with electronic reverse device. To use Reverse Connector proceed as follows:

1. Unplug existing sea level cap from the ECM.
2. Plug-in the reverse connector.



REVERSE CONNECTOR

GRAND TOURING SPORT 550F (CAN/US AND EUROPE) / RENEGADE™ SPORT 550F (CAN/US AND EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Yellow(P/N 414 748 600)					
Ramp	600 (P/N 417 222 444)					
Calibration Screw Position	3	4	2	3	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM \pm 100	3000					
Maximum RPM \pm 100	6800					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Brown (P/N 417 127 061)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° (P/N 417 126 574)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	190	180	170	160	140	130	1
	PTO	200	190					1
Jet needle		6BFY46						2
MAG Needle position		3		2				—
PTO Needle position		4		2				
Slide cut-away		2.5						2
Pilot jet		35		45		55		2
MAG mixture screw		1.25						—
PTO mixture screw		1		1.25				—
Valve seat		1.2						2
Needle jet		P-8 (159)				P-6 (159)		2
Float level (± 1 mm)		23.9						—
Idle RPM (± 200)		1650						—
Idle throttle valve position (± 0.1 mm)		1.6		1.8	2	2.2	2.4	—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
-40°C (-40°F)	MAG	200	190	180	170	150	140
	PTO	210	200				
-30°C (-22°F)	MAG	195	185	175	165	145	135
	PTO	205	195				
-20°C (-4°F)	MAG	190	180	170	160	140	130
	PTO	200	190				
-10°C (14°F)	MAG	185	175	165	155	135	125
	PTO	195	185				
0°C (32°F)	MAG	180	170	160	150	130	120
	PTO	190	180				
10°C (50°F)	MAG	175	165	155	145	125	115
	PTO	185	175				
20°C (68°F)	MAG	170	160	150	140	120	110
	PTO	180	170				
TEMPERATURE	CARBURATOR	MAIN JETS					

Additional Information

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Reverse connector	(P/N 515 174 800)		(P/N 515 174 700) Connect to ECM				
INFOS	ADJUSTMENT						

MX Z™ SPORT 550F / MX Z TNT™ 550F (CAN/US AND EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Orange (P/N 414 639 000)		Purple/Blue(P/N 415 034 900)			
Ramp	412 (P/N 417 222 515)					
Calibration Screw Position	3	4	2	3	4	5
Pin	Short no thread 32 mm 9,9 g (P/N 417 004 309)					
Engagement RPM ± 100	3900					
Maximum RPM ± 100	6800					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Brown (P/N 417 127 061)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	44° (P/N 417 126 574)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	190	180	170	160	140	130	1
	PTO	200	190					1
Jet needle		6BFY46						2
MAG Needle position		3		2				—
PTO Needle position		4		2				
Slide cut-away		2.5						2
Pilot jet		35		45		55		2
MAG mixture screw		1.25						—
PTO mixture screw		1		1.25				
Valve seat		1.2						2
Needle jet		P-8 (159)				P-6 (159)		2
Float level (± 1 mm)		23.9						—
Idle RPM (± 200)		1650						—
Idle throttle valve position (± 0.1 mm)		1.6		1.8	2	2.2	2.4	—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
-40°C (-40°F)	MAG	200	190	180	170	150	140
	PTO	210	200				
-30°C (-22°F)	MAG	195	185	175	165	145	135
	PTO	205	195				
-20°C (-4°F)	MAG	190	180	170	160	140	130
	PTO	200	190				
-10°C (14°F)	MAG	185	175	165	155	135	125
	PTO	195	185				
0°C (32°F)	MAG	180	170	160	150	130	120
	PTO	190	180				
10°C (50°F)	MAG	175	165	155	145	125	115
	PTO	185	175				
20°C (68°F)	MAG	170	160	150	140	120	110
	PTO	180	170				
TEMPERATURE	CARBURATOR	MAIN JETS					

Additional Information

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Reverse connector	(P/N 515 174 800)	(P/N 515 174 700) Connect to ECM					
INFOS	ADJUSTMENT						

**EXPEDITION® SPORT 550F /
 SKANDIC™ TUNDRA™ 550F /
 SKANDIC TUNDRA SPORT 550F /
 SKANDIC TUNDRA LT 550F (CAN/US AND EUROPE)**

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/Yellow (P/N 414 817 500)					
Ramp	600 (P/N 417 222 444)					
Calibration Screw Position	3	4	2	3	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM ± 100	2400					
Maximum RPM ± 100	6800					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Brown (P/N 417 127 061)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	44° (P/N 417 126 574)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	190	180	170	160	140	130	1
	PTO	200	190					1
Jet needle		6BFY46						2
MAG needle position		3		2				—
PTO needle position		4		2				
Slide cut-away		2.5						2
Pilot jet		35		45		55		2
MAG mixture screw		1.25						—
PTO mixture screw		1		1.25				
Valve seat		1.2						2
Needle jet		P-8 (159)				P-6 (159)		2
Float level (± 1 mm)		23.9						—
Idle RPM (± 200)		1650						—
Idle throttle valve position (± 0.1 mm)		1.6		1.8	2	2.2	2.4	—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
-40°C (-40°F)	MAG	200	190	180	170	150	140
	PTO	210	200				
-30°C (-22°F)	MAG	195	185	175	165	145	135
	PTO	205	195				
-20°C (-4°F)	MAG	190	180	170	160	140	130
	PTO	200	190				
-10°C (14°F)	MAG	185	175	165	155	135	125
	PTO	195	185				
0°C (32°F)	MAG	180	170	160	150	130	120
	PTO	190	180				
10°C (50°F)	MAG	175	165	155	145	125	115
	PTO	185	175				
20°C (68°F)	MAG	170	160	150	140	120	110
	PTO	180	170				
TEMPERATURE	CARBURATOR	MAIN JETS					

Additional Information

		ALTITUDE				
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft
Reverse connector		(P/N 515 174 800)			(P/N 515 174 700) Connect to ECM	
INFOS		ADJUSTMENT				

SKANDIC WT 550F (YETI II)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Green (P/N 414 742 100)					
Ramp	600 (P/N 417 222 444)					
Calibration Screw Position	3	4	5	3	4	
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM \pm 100	2800	3000	3200	3400		
Maximum RPM \pm 100	6900					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Orange/Blue/Blue (P/N 417 119 100)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	8 kgf (17.6 lbf)					
Cam angle (degrees)	40° - 30° (P/N 619 100 035)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	190	180	170	160	150	140	1
	PTO							1
Jet needle		6BFY46						2
Needle position		2			1			—
Slide cut-away		2.0						2
Pilot jet		40						2
Mixture screw		2.5			2			—
Valve seat		1.2						2
Needle jet		P-8 (159)						2
Float level (± 1 mm)		23.9						—
Idle RPM (± 200)		1650						—
Idle throttle valve position (± 0.1 mm)		1.5	1.7	1.8	2	2.1	2.2	—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
-40°C (-40°F)	MAG	210	200	190	180	170	160
	PTO						
-30°C (-22°F)	MAG	200	190	180	170	160	150
	PTO						
-20°C (-4°F)	MAG	190	180	170	160	150	140
	PTO						
-10°C (14°F)	MAG	180	170	160	150	140	130
	PTO						
0°C (32°F)	MAG	170	160	150	140	130	120
	PTO						
10°C (50°F)	MAG	160	150	140	130	120	110
	PTO						
20°C (68°F)	MAG	150	140	130	120	110	100
	PTO						
TEMPERATURE	CARBURATOR	MAIN JETS					

GRAND TOURING SPORT 600

Drive Pulley

ALTIMUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Purple (P/N 414 817 800)			Pink/Purple (P/N 414 754 200)		
Ramp	412 (P/N 417 222 515)					
Calibration Screw Position	3	4	5	4	5	6
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM \pm 100	3400		3900			
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTIMUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Black (P/N 417 127 039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42° (P/N 417 127 012)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

ALTITUDE								
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	420	390	360	330	300	280	1
	PTO							1
Jet needle		9CEY2-58						2
Needle position		2						—
Slide cut-away		2.0						2
Pilot jet		17.5						2
Mixture screw		1.5			2			—
Valve seat		1.5						2
Needle jet		P-0M						2
Float level (± 1 mm)		N/A						—
Idle RPM (± 200)		1600						—
Idle throttle valve position (± 0.1 mm)		1.5	1.6	1.7	1.8	1.9		—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

ALTITUDE								
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
-40°C (-40°F)	MAG	440	410	380	350	320	300	
	PTO							
-30°C (-22°F)	MAG	430	400	370	340	310	290	
	PTO							
-20°C (-4°F)	MAG	420	390	360	330	300	280	
	PTO							
-10°C (14°F)	MAG	410	380	350	320	290	270	
	PTO							
0°C (32°F)	MAG	400	370	340	310	280	260	
	PTO							
10°C (50°F)	MAG	390	360	330	300	270	250	
	PTO							
20°C (68°F)	MAG	380	350	320	290	260	240	
	PTO							
TEMPERATURE	CARBURATOR	MAIN JETS						

MX Z SPORT 600 / MX Z TNT 600

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Purple/Purple (P/N 414 817 900)			Pink/Purple (P/N 414 754 200)		
Ramp	412 (P/N 417 222 515)					
Calibration Screw Position	3	4	5	4	5	6
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM \pm 100	3800			3900	4100	
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Black (P/N 417 127 039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42° (P/N 417 127 012)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	420	390	360	330	300	280	1
	PTO							1
Jet needle		9CEY2-58						2
Needle position		2						—
Slide cut-away		2.0						2
Pilot jet		17.5						2
Mixture screw		1.5			2			—
Valve seat		1.5						2
Needle jet		P-0M						2
Float level (± 1 mm)		N/A						—
Idle RPM (± 200)		1600						—
Idle throttle valve position (± 0.1 mm)		1.5	1.6	1.7	1.8	1.9		—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
-40°C (-40°F)	MAG	440	410	380	350	320	300
	PTO						
-30°C (-22°F)	MAG	430	400	370	340	310	290
	PTO						
-20°C (-4°F)	MAG	420	390	360	330	300	280
	PTO						
-10°C (14°F)	MAG	410	380	350	320	290	270
	PTO						
0°C (32°F)	MAG	400	370	340	310	280	260
	PTO						
10°C (50°F)	MAG	390	360	330	300	270	250
	PTO						
20°C (68°F)	MAG	380	350	320	290	260	240
	PTO						
TEMPERATURE	CARBURATOR	MAIN JETS					

SUMMIT™ SPORT 146" 600

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Pink (P/N 414 916 300)		Green/Pink (P/N 414 756 900)			
Ramp	417 (P/N 417 222 552)					
Calibration Screw Position	3	4	2	3	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)		Short threaded 32 mm/10,88 g (P/N 417 222 477) 1 x set screw 20 mm (P/N 206 262 099)		Short threaded 32 mm/10,88 g (P/N 417 222 477)	
Engagement RPM \pm 100	3400		4100			
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Black (P/N 417 127 039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	43° - 47° (P/N 417 127 133)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

ALTITUDE								
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	420	390	360	330	300	280	1
	PTO							1
Jet needle		9CEY2-58						2
Needle position		2						—
Slide cut-away		2.0						2
Pilot jet		17.5						2
Mixture screw		1.5			2			—
Valve seat		1.5						2
Needle jet		P-0M						2
Float level (± 1 mm)		N/A						—
Idle RPM (± 200)		1600						—
Idle throttle valve position (± 0.1 mm)		1.5	1.6	1.7	1.8	1.9		—
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

ALTITUDE								
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
-40°C (-40°F)	MAG	440	410	380	350	320	300	
	PTO							
-30°C (-22°F)	MAG	430	400	370	340	310	290	
	PTO							
-20°C (-4°F)	MAG	420	390	360	330	300	280	
	PTO							
-10°C (14°F)	MAG	410	380	350	320	290	270	
	PTO							
0°C (32°F)	MAG	400	370	340	310	280	260	
	PTO							
10°C (50°F)	MAG	390	360	330	300	270	250	
	PTO							
20°C (68°F)	MAG	380	350	320	290	260	240	
	PTO							
TEMPERATURE	CARBURATOR	MAIN JETS						

Vehicle Calibration

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Stopper Strap		4		3		2
REAR SUSPENSION	ADJUSTMENT					

EXPEDITION LE 600 H.O. E-TEC® / EXPEDITION SE 600 H.O. E-TEC / SKANDIC WT 600 H.O. E-TEC (REV-XU™)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Red (P/N 414 993 000)					
Ramp	600 (P/N 417 222 444)					
Calibration Screw Position	2	3	4	2	3	4
Pin	Long solid 35.75 mm/18,8 g (P/N 417 222 594)			Short threaded 32 mm/10,88 g (P/N 417 222 477) 1 X set screw 16 mm (P/N 206 261 699)		
Engagement RPM ± 100	3000					
Maximum RPM ± 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	White 2 (P/N 417 127 243)					
Spring tension Kg ± 0.7 (lb ± 1.5)	6.8 kgf (15 lbf)					
Cam angle (degrees)	40° (P/N 417 127 205)					
CLUTCHING	ADJUSTMENT					

GSX™ LE 600 H.O. E-TEC®

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Green (P/N 414 742 100)			Blue/Yellow (P/N 414 689 500)		
Ramp	412 (P/N 417 222 515)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM \pm 100	3400			3600		
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	48° (P/N 417 127 083)			42° - 40° (P/N 417 127 106)		
CLUTCHING	ADJUSTMENT					

GRAND TOURING LE 600 H.O. E-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/Green (P/N 414 689 200)			Blue/Yellow (P/N 414 689 500)		
Ramp	414 (P/N 417 222 546)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short no thread 32 mm/9,9 g (P/N 417 004 309)		
Engagement RPM \pm 100	3400			3600		
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	48° (P/N 417 127 083)			42° - 40° (P/N 417 127 106)		
CLUTCHING	ADJUSTMENT					

**MX Z TNT 600 H.O. E-TEC /
 MX Z™ X™ 600 H.O. E-TEC /
 MX Z X-RS™ 600 H.O. E-TEC (CAN/US AND EUROPE) /
 RENEGADE ADRENALINE 600 H.O.
 E-TEC (CAN/US AND EUROPE) /
 RENEGADE™ BACKCOUNTRY™ 600 H.O. E-TEC /
 RENEGADE BACKCOUNTRY X 600
 H.O. E-TEC (CAN/US AND EUROPE) /
 RENEGADE X 600 H.O. E-TEC**

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Green (P/N 414 817 700)			Purple/Yellow (P/N 415 015 300)		
Ramp	412 (P/N 417 222 515)					
Calibration Screw Position	3	4	5	2	3	4
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)			Short threaded 32 mm/10.88 g (P/N 417 222 477)		
Engagement RPM \pm 100	3400			3800		
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	48° (P/N 417 127 083)			42° - 40° (P/N 417 127 106)		
CLUTCHING	ADJUSTMENT					

SKANDIC TUNDRA Xtreme 600 H.O. E-TEC (CAN/US AND EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/Orange (P/N 415 015 200)		Blue/Green (P/N 414 817 700)			
Ramp	412 (P/N 417 222 515)		440 (P/N 417 223 096)			
Calibration Screw Position	3	4	2	3	3	4
Pin	Short threaded 32 mm/10,88 g (P/N 417 222 477) 1 X set screw 16 mm (P/N 206 261 699)				Short threaded 32 mm/10,88 g (P/N 417 222 477)	
Engagement RPM \pm 100	2800					
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Black (P/N 417 127 039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42° (P/N 417 127 012)					
CLUTCHING	ADJUSTMENT					

Vehicle Calibration

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Stopper Strap	3					
Rear suspension extension	Locked		Free			
REAR SUSPENSION	ADJUSTMENT					

SUMMIT EVEREST™ 146" 600 H.O. E-TEC / SUMMIT X 154" 600 H.O. E-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Green (P/N 414 817 700)		Purple/Green (P/N 415 015 400)			
Ramp	412 (P/N 417 222 515)		440 (P/N 417 223 096)			
Calibration Screw Position	3	4	3	4	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)		Short threaded 32 mm/10,88 g (P/N 417 222 477) 1 x set screw/16 mm (P/N 206 261 699)		Short threaded 32 mm/10,88 g (P/N 417 222 477)	
Engagement RPM ± 100	4000					
Maximum RPM ± 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Black (P/N 417 127 039)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	41° - 45° (P/N 417 127 105)					
CLUTCHING	ADJUSTMENT					

Vehicle Calibration

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Stopper Strap		4		3		2
REAR SUSPENSION	ADJUSTMENT					

SUMMIT EVEREST 146" 600 H.O. E-TEC (EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Green (P/N 414 817 700)		Purple/Green (P/N 415 015 400)			
Ramp	412 (P/N 417 222 515)		440 (P/N 417 223 096)			
Calibration Screw Position	3	4	3	4	4	5
Pin	Short solid 32 mm/16,75 g (P/N 417 004 308)		Short threaded 32 mm/10,88 g (P/N 417 222 477) 1 x set screw 16 mm (P/N 206 261 699)		Short threaded 32 mm/10,88 g (P/N 417 222 477)	
Engagement RPM \pm 100	4000					
Maximum RPM \pm 100	8100					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Black (P/N 417 127 039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	41° - 45° (P/N 417 127 105)					
CLUTCHING	ADJUSTMENT					

Vehicle Calibration

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Stopper Strap		4		3		2
REAR SUSPENSION	ADJUSTMENT					

MX Z TNT 800R POWER TEK

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Purple/Blue (P/N 415 034 900)					
Ramp	414 (P/N 417 222 546)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Long threaded 35,75 mm/12,4 g (P/N 417 222 595) 1 x set screw, 20 mm (P/N 206 262 099)		
Engagement RPM \pm 100	3800					
Maximum RPM \pm 100	8200					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 44° (P/N 417 127 109)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Main jet	MAG	480					1
	PTO	480					1
Jet needle		9EGI04-58					2
Needle position		N/A					—
Slide cut-away		2.0					2
Pilot jet		17,5					2
Mixture screw		1.5					—
Valve seat		1.5					2
Needle jet		P-0M					2
Float level (± 1 mm)		N/A					—
Idle RPM (± 200)		1600					—
Idle throttle valve position (± 0.1 mm)		1.6	1.8		2		—
CALIBRATION		ADJUSTMENT					QTY

Main Jet Chart

		ALTITUDE										
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft					
-40°C (-40°F)	MAG	520 N										
	PTO	520 N										
-30°C (-22°F)	MAG	500										
	PTO	500										
-20°C (-4°F)	MAG											
	PTO											
-10°C (14°F)	MAG											
	PTO											
0°C (32°F)	MAG						480					
	PTO						480					
10°C (50°F)	MAG						480					
	PTO						480					
20°C (68°F)	MAG						480					
	PTO						480					
TEMPERATURE	CARBURATOR	MAIN JETS										

RENEGADE ADRENALINE 800R POWER TEK / RENEGADE SP 800R POWER TEK

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Purple/Blue (P/N 415 034 900)					
Ramp	414 (P/N 417 222 546)			413 (P/N 417 222 508)		
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Long threaded 35,75 mm/12,4 g(P/N 417 222 595) 1 x set screw/12 mm (P/N 206 261 299)		
Engagement RPM \pm 100	3800		3900	4000		4100
Maximum RPM \pm 100	8200					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° - 42° (P/N 417 126 973)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Main jet	MAG	480					1
	PTO	480					1
Jet needle		9EGI04-58					2
Needle position		N/A					—
Slide cut-away		2.0					2
Pilot jet		17,5					2
Mixture screw		1.5					—
Valve seat		1.5					2
Needle jet		P-0M					2
Float level (± 1 mm)		N/A					—
Idle RPM (± 200)		1600					—
Idle throttle valve position (± 0.1 mm)		1.6	1.8		2		—
CALIBRATION		ADJUSTMENT					QTY

Main Jet Chart

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
-40°C (-40°F)	MAG	520 N					
	PTO	520 N					
-30°C (-22°F)	MAG	500					
	PTO	500					
-20°C (-4°F)	MAG	480					
	PTO						
-10°C (14°F)	MAG						
	PTO						
0°C (32°F)	MAG						
	PTO						
10°C (50°F)	MAG						
	PTO						
20°C (68°F)	MAG						
	PTO						
TEMPERATURE	CARBURATOR	MAIN JETS					

RENEGADE™ BACKCOUNTRY™ 800R POWER TEK

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Purple/Blue (P/N 415 034 900)					
Ramp	413 (P/N 417 222 508)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Long threaded 35,75 mm/12,4 g(P/N 417 222 595) 1 set screw 12 mm (P/N 206 261 299)		
Engagement RPM \pm 100	3800		3900	4000		4100
Maximum RPM \pm 100	8200					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° - 42° (P/N 417 126 973)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	480						1
	PTO							1
Jet needle		9EGI04-58						2
Needle position		N/A						—
Slide cut-away		2.0						2
Pilot jet		17,5						2
Mixture screw		1.5						—
Valve seat		1.5						2
Needle jet		P-0M						2
Float level (± 1 mm)		N/A						—
Idle RPM (± 200)		1600						—
Idle throttle valve position (± 0.1 mm)		1.6		1.8		2	—	
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE											
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft						
-40°C (-40°F)	MAG	520 N											
	PTO												
-30°C (-22°F)	MAG	500											
	PTO												
-20°C (-4°F)	MAG												
	PTO												
-10°C (14°F)	MAG												
	PTO												
0°C (32°F)	MAG							480					
	PTO												
10°C (50°F)	MAG												
	PTO												
20°C (68°F)	MAG												
	PTO												
TEMPERATURE	CARBURATOR	MAIN JETS											

SUMMIT EVEREST 146", 154" & 163" 800R POWER TEK / SUMMIT SP 154" 800R POWER TEK

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Purple (P/N 414 817 800)		Green/Purple (P/N 414 762 800)			
Ramp	413 (P/N 417 222 508)		441 (P/N 417 223 098)			
Calibration Screw Position	3	4	3	4		5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)		Long threaded 35,75 mm/12,4 g (P/N 417 222 595) 1 set screw/12 mm(P/N 206 261 299)		Short threaded 32 mm/10,88 g (P/N 417 222 477)	
Engagement RPM \pm 100	3800					
Maximum RPM \pm 100	8200					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Purple (P/N 417 127 062)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	43° - 47° (P/N 417 127 133)					
CLUTCHING	ADJUSTMENT					

Carburetion (Refer to appropriate Specification Booklet for part numbers)

NOTICE These adjustments are guidelines only. Specific adjustments vary with temperature, altitude and snow condition. Always observe spark plug condition for proper jetting.

		ALTITUDE						
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Main jet	MAG	480						1
	PTO							1
Jet needle		9EGI04-58						2
Needle position		N/A						—
Slide cut-away		2.0						2
Pilot jet		17,5						2
Mixture screw		1.5						—
Valve seat		1.5						2
Needle jet		P-0M						2
Float level (± 1 mm)		N/A						—
Idle RPM (± 200)		1900						—
Idle throttle valve position (± 0.1 mm)		1.6		1.8		2	—	
CALIBRATION		ADJUSTMENT						QTY

Main Jet Chart

		ALTITUDE											
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft						
-40°C (-40°F)	MAG	520 N											
	PTO												
-30°C (-22°F)	MAG	500											
	PTO												
-20°C (-4°F)	MAG												
	PTO												
-10°C (14°F)	MAG												
	PTO												
0°C (32°F)	MAG							480					
	PTO												
10°C (50°F)	MAG												
	PTO												
20°C (68°F)	MAG												
	PTO												
TEMPERATURE	CARBURATOR							MAIN JETS					

Vehicle Calibration

ALTITUDE						
Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Stopper Strap	4		3		2	

MX Z TNT 800R E-TEC / MX Z X 800R E-TEC / MX Z X-RS 800R E-TEC (CAN/US AND EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Green (P/N 414 817 700)		Purple/Yellow (P/N 415 015 300)			
Ramp	414 (P/N 417 222 546)					
Calibration Screw Position	3	4	2	3	4	5
Pin	Long solid 35.75 mm/18.8 g (P/N 417 222 594)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595) 1 x set screw 12 mm (P/N 206 261 299)			
Engagement RPM \pm 100	3800					
Maximum RPM \pm 100	8000					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 44° (P/N 417 127 109)					
CLUTCHING	ADJUSTMENT					

RENEGADE ADRENALINE 800R E-TEC / RENEGADE X 800R E-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Blue/Green (P/N 414 817 700)		Purple/Yellow (P/N 415 015 300)			
Ramp	414 (P/N 417 222 546)			413 (P/N 417 222 508)		
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35.75 mm/18.8 g (P/N 417 222 594)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595) 1 x set screw 12 mm (P/N 206 261 299)			
Engagement RPM \pm 100	3800		3900	4000		4100
Maximum RPM \pm 100	8000					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° - 42° (P/N 417 126 973)					
CLUTCHING	ADJUSTMENT					

RENEGADE BACKCOUNTRY 800R E-TEC / RENEGADE BACKCOUNTRY X 800R E-TEC (CAN/US AND EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Violet/Blue (P/N 415 034 900)		Purple/Yellow (P/N 415 015 300)			
Ramp	413 (P/N 417 222 508)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35.75 mm/18.8 g (P/N 417 222 594)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595) 1 x set screw 12 mm (P/N 206 261 299)			
Engagement RPM \pm 100	3800		3900	4000		4100
Maximum RPM \pm 100	8000					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Green (P/N 417 127 137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° - 42° (P/N 417 126 973)					
CLUTCHING	ADJUSTMENT					

SUMMIT EVEREST 154" 800R E-TEC / SUMMIT FREERIDE™ 154" 800R E-TEC / SUMMIT X 146", 154" & 163" 800R E-TEC

Drive Pulley

ALTITUDE						
Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	▶1800 m 6000 ft◀	2400 m 8000 ft	3000 m 10000 ft	
Spring	Blue/Purple (P/N 414 817 800)		Purple/Pink (P/N 414 949 500)			
Ramp	413 (P/N 417 222 508)		441 (P/N 417 223 098)			
Calibration Screw Position	3	4	3	4	3	4
Pin	Long solid 35.75 mm/18.8 g (P/N 417 222 594)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595) 1 x set screw 12 mm (P/N 206 261 299)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595)	
Engagement RPM ± 100	3800					
Maximum RPM ± 100	8000					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	▶1800 m 6000 ft◀	2400 m 8000 ft	3000 m 10000 ft	
Spring	Purple (P/N 417 127 062)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	43° - 47° (P/N 417 127 133)					
CLUTCHING	ADJUSTMENT					

Vehicle Calibration

ALTITUDE						
Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	▶1800 m 6000 ft◀	2400 m 8000 ft	3000 m 10000 ft	
Stopper Strap	4		3		2	
REAR SUSPENSION	ADJUSTMENT					

SUMMIT FREERIDE 154" 800R E-TEC (EUROPE) / SUMMIT X 146", 154" & 163" 800R E-TEC (EUROPE)

Drive Pulley

ALTITUDE							
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Spring	Blue/Purple (P/N 414 817 800)		Purple/Pink (P/N 414 949 500)				
Ramp	413 (P/N 417 222 508)		441 (P/N 417 223 098)				
Calibration Screw Position	3	4	3	4	3	4	
Pin	Long solid 35.75 mm/18.8 g (P/N 417 222 594)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595) 1 x set screw 12 mm (P/N 206 261 299)		Long threaded 35.75 mm/12.4 g (P/N 417 222 595)		
Engagement RPM \pm 100	3800						
Maximum RPM \pm 100	8000						
CLUTCHING	ADJUSTMENT						

Driven Pulley

ALTITUDE							
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Spring	Purple (P/N 417 127 062)						
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A						
Cam angle (degrees)	43° - 47° (P/N 417 127 133)						
CLUTCHING	ADJUSTMENT						

Vehicle Calibration

ALTITUDE							
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft	
Stopper Strap		4		3		2	
REAR SUSPENSION	ADJUSTMENT						

SKANDIC SWT V-800 (YETI II)

Drive Pulley

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/Red (P/N 414 689 800)						
Ramp	614 (P/N 417 222 883)						
Calibration Screw Position	3	4	6	5			
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Short no thread 32 mm/9,9 g (P/N 417 004 309)			
Engagement RPM \pm 100	2500						
Maximum RPM \pm 100	7250						
CLUTCHING	ADJUSTMENT						

Driven Pulley

		ALTITUDE					
		Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Orange/Gold/Gold (M140069)						
Spring tension Kg \pm 0.7 (lb \pm 1.5)	7.7 kgf (17 lbf)						
Cam angle (degrees)	40° - 30° (P/N 619 100 035)						
CLUTCHING	ADJUSTMENT						

**EXPEDITION SPORT 600 ACE™ /
RENEGADE™ SPORT 600 ACE
(CAN/US AND EUROPE) /
SKANDIC TUNDRA LT 600 ACE (CAN/US
AND EUROPE)**

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/White (P/N 417 223 314)	Red/Red (P/N 417 223 186)		Red/Yellow (P/N 417 223 315)	Red/Orange (P/N 417 223 316)	Red/Green (P/N 417 223 459)
Ramp	716 (P/N 417 223 450)		720 (P/N 417 223 498)			
Ramp quantity	6					
Engagement RPM ± 100	2200					
Maximum RPM ± 100	7250					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)					
Spring tension Kg ± 0.7 (lb ± 1.5)	6.4 kgf (14.1 lbf)					
Cam angle (degrees)	41°-45° (P/N 417 127 235)					
CLUTCHING	ADJUSTMENT					

GRAND TOURING SPORT 600 ACE / MX Z SPORT 600 ACE

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/Yellow (P/N 417 223 315)	Red/Orange (P/N 417 223 316)	Red/Red (P/N 417 223 186)	Red/Yellow (P/N 417 223 315)	Red/Orange (P/N 417 223 316)	Red/Green (P/N 417 223 459)
Ramp	712 (P/N 417 223 448)		720 (P/N 417 223 498)			
Ramp quantity	6					
Engagement RPM \pm 100	2200					
Maximum RPM \pm 100	7250					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	6.4 kgf (14.1 lbf)					
Cam angle (degrees)	41°-45° (P/N 417 127 235)					
CLUTCHING	ADJUSTMENT					

GRAND TOURING SPORT 600 ACE (EUROPE) / MX Z TNT 600 ACE

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/White (P/N 417 223 314)	Red/Red (P/N 417 223 186)		Red/Yellow (P/N 417 223 315)	Red/Orange (P/N 417 223 316)	Red/Green (P/N 417 223 459)
Ramp	715 (P/N 417 223 452)		720 (P/N 417 223 498)			
Ramp quantity	6					
Engagement RPM \pm 100	2200					
Maximum RPM \pm 100	7250					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	6.4 kgf (14.1 lbf)					
Cam angle (degrees)	41°-45° (P/N 417 127 235)					
CLUTCHING	ADJUSTMENT					

SKANDIC WT 600 ACE (REV-XU)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/White (P/N 417 223 314)	Red/Red (P/N 417 223 186)		Red/Yellow (P/N 417 223 315)	Red/Orange (P/N 417 223 316)	Red/Green (P/N 417 223 459)
Ramp	716 (P/N 417 223 450)		720 (P/N 417 223 498)			
Ramp quantity	6					
Engagement RPM \pm 100	2200					
Maximum RPM \pm 100	7250					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	6.4 kgf (14.1 lbf)					
Cam angle (degrees)	37°-45° (P/N 417 127 240)					
CLUTCHING	ADJUSTMENT					

EXPEDITION LE 1200 4-TEC® / EXPEDITION SE 1200 4-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Red/Orange (P/N 414 015 200)					
Ramp	617 (P/N 417 223 088)					
Calibration Screw Position	2	3	4	3	4	5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Long threaded 35,75 mm/12,4 g (P/N 417 222 595)		
Engagement RPM ± 100	2500			2800		
Maximum RPM ± 100	7800					
CLUTCHING	ADJUSTMENT					

Driven Pulley





ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Beige 2 (P/N 417 127 242)					
Spring tension Kg ± 0.7 (lb ± 1.5)	7.5 kgf (16.5 lbf)					
Cam angle (degrees)	44° - 40° (P/N 417 127 206)					
CLUTCHING	ADJUSTMENT					

GSX LE 1200 4-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Orange (P/N 414 689 700)			Yellow/Blue (P/N 414 818 000)		
Ramp	617 (P/N 417 223 088)					
Calibration Screw Position	3	4	5	4	5	6
Pin	Long solid 35,75 mm/18,8g (P/N 417 222 594)			Short solid 32 mm/16,75g (P/N 417 004 308)		
Engagement RPM \pm 100	2500			2800		
Maximum RPM \pm 100	7800					
CLUTCHING	ADJUSTMENT					

Driven Pulley





ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)			Beige 2 (P/N 417 127 242)		
Spring tension Kg \pm 0.7 (lb \pm 1.5)	7.5 kgf (16.5 lbf)					
Cam angle (degrees)	47° - 40°  (P/N 417 127 190) 			44°  (P/N 417 127 169) 		
CLUTCHING	ADJUSTMENT					

GRAND TOURING LE 1200 4-TEC / GRAND TOURING SE 1200 4-TEC (CAN/US AND EUROPE) / GSX SE 1200 4-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Orange (P/N 414 689 700)			Yellow/Blue (P/N 414 818 000)		
Ramp	617 (P/N 417 223 088)					
Calibration Screw Position	3	4	5	3		
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Short solid 32 mm/16,75 g (P/N 417 004 308)		
Engagement RPM \pm 100	2500			2800		
Maximum RPM \pm 100	7800					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)			Beige 2 (P/N 417 127 242)		
Spring tension Kg \pm 0.7 (lb \pm 1.5)	7.5 kgf (16.5 lbf)					
Cam angle (degrees)	47° - 40°  (P/N 417 127 190) 			44°  (P/N 417 127 169) 		
CLUTCHING	ADJUSTMENT					

MX Z TNT 1200 4-TEC / MX Z X 1200 4-TEC

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Orange (P/N 414 689 700)			Yellow/Blue (P/N 414 818 000)		
Ramp	617 (P/N 417 223 088)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Long threaded 35,75 mm/12,4 g (P/N 417 222 595)		
Engagement RPM ± 100	2500			2800		
Maximum RPM ± 100	7800					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2(P/N 417 127 236)			Beige 2 (P/N 417 127 242)		
Spring tension Kg ± 0.7 (lb ± 1.5)	7.5 kgf (16.5 lbf)					
Cam angle (degrees)	47° - 40° ►(P/N 417 127 190)◄			44° ►(P/N 417 127 169)◄		
CLUTCHING	ADJUSTMENT					

RENEGADE ADRENALINE 1200 4-TEC / RENEGADE X 1200 4-TEC (CAN/US AND EUROPE)

Drive Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Yellow/Orange (P/N 414 689 700)			Yellow/Blue (P/N 414 818 000)		
Ramp	617 (P/N 417 223 088)					
Calibration Screw Position	3	4	5	3	4	5
Pin	Long solid 35,75 mm/18,8 g (P/N 417 222 594)			Short threaded 32 mm/10,88 g (P/N 417 222 477)		
Engagement RPM ± 100	2500			2800		
Maximum RPM ± 100	7800					
CLUTCHING	ADJUSTMENT					

Driven Pulley

ALTITUDE						
	Sea level 0 m (ft)	600 m 2000 ft	1200 m 4000 ft	1800 m 6000 ft	2400 m 8000 ft	3000 m 10000 ft
Spring	Pink 2 (P/N 417 127 236)			Beige 2 (P/N 417 127 242)		
Spring tension Kg ± 0.7 (lb ± 1.5)	7.5 kgf (16.5 lbf)					
Cam angle (degrees)	47° - 40° ▶(P/N 417 127 190)◀			44° ▶(P/N 417 127 169)◀		
CLUTCHING	ADJUSTMENT					