



ProLine Rakes

Kubota's RA2577 is a ProLine side delivery double rotor rake. ProLine rakes feature a drive system, which houses oil-immersed pinion and crown wheels. The fully enclosed design of the gearbox ensures full and permanent lubrication, making the entire system absolutely maintenance-free. Our extensive experience guarantees that our machines come with well-proven technology. The hardened cam track is adjustable, and with a large 15'7" diameter, it gives positive guidance to the steel rotors and reduces the machine's noise level.

Kubota TerraLink Quattro System



The Kubota TerraLink Quattro System provides perfect ground contour following in three dimensions. The trailed axle configuration enhances quiet running and reduces tractor input power, particularly in wet conditions. It provides superb stability on slopes and while tracking during road transport. And is absolutely maintenance and wear-free.



Unique Maneuverability

Kubota's side delivery rotary rake model has carrier frames that allow for controlled rear steering, allowing the rake to make turns up to 80 degrees. This is ideal for making tight turns on headlands and productive swathing, even in awkwardly shaped fields. When in headland position, an outstanding lifting height of 18", prevents swath damage. And with a lower center of gravity, this model has excellent stability.



High Capacity Working Width

The RA2577 ProLine double rotor rake delivers a working width of 25'3". The high capacity side delivery concept adds excellent flexibility in swath formation and allows you to collect crop from a working width of up to 49'3" into one swath.



Maintenance Free ProLine Gearbox

Kubota RA2577 Rakes are fitted with the renowned ProLine gearbox, with its maintenance-free oil bath solution. The shape of the massive 15.7" curve disc allows the tine arms to leave the crop faster, leaving a more uniform swath shape.



Exceptional Raking Performance

The RA2577 rotors features 12 tine arms on the front rotor, each with 4 tines, and 13 tine arms, each with 5 tines on the rear rotor. This ensures more accurate raking performance and allows higher forward speed.



Outstanding Durability

The Kubota rakes are equipped for maximum raking performance. The RA2577 rakes include heavy duty 0.39" wire diameter tines for outstanding durability.



Fast and Safe Transport

For fast and safe transport from field to field, RA2577 can be optionally equipped with a hydraulic swath board. The transport width of this model is 9'9".