

Pursuit <sup>®</sup>	
Model number:	SC713
Weight capacity:	400 lbs.
Maximum speed <sup>1</sup> :	Up to 7.25 mph
Ground clearance <sup>2</sup> :	3.56"
Turning radius:	67.25"
Overall length <sup>2</sup> :	53.25"
Overall width <sup>2</sup> :	25.25"
Front tires:	13" solid
Rear tires:	13" solid
Seat to deck:	17"-18.25"
Suspension:	Front & Rear
Range per charge <sup>1</sup> :	Up to 14 miles
Seat-to-ground:	24.75" - 26.25"
Total weight without batteries:	218.5 lbs.
Heaviest piece when disassembled:	95 lbs. (front section)
Standard seating:	Type: Deluxe reclining high-back seat with headrest
	Weight: 39.5 lbs.  Material: Black Vinyl
	Dimensions: width - 19" (overall width) depth - 17" (effective depth)
Drivetrain:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual braking system:	Regenerative and electromechanical
Battery requirements <sup>3</sup> :	Two 12-volt, deep cycle Size: NF-22
Battery weight:	NF-22: 38 lbs. each
Battery charger:	5-amp, off-board

## Features

- Infinitely-adjustable tiller angle w/conveniently located handle
- · Feather-touch disassembly
- Powerful drivetrain; features 120 amp microprocessor based controller
- 24V, 4-pole DC motor for increased power
- Deluxe reclining high-back seat with headrest and sliders
- Full lighting package including directional signals and angleadjustable, lower headlight
- Delta tiller with wraparound handles
- Large 13" low-profile solid tires for excellent outdoor performance
- Front and rear suspension
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- Rearview mirror standard

## **Options**

- · Rear basket
- · Safety flag
- Durable weather cover
- Group 24 batteries











Silve

Colors:

NOTE: All specifications subject to change without notice



The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed & range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %.

800-800-8586 (US) • 888-570-1113 (Canada) • www.pridemobility.com



Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition

<sup>&</sup>lt;sup>2</sup>Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%)

<sup>&</sup>lt;sup>3</sup>AGM or Gel-Cell type required

<sup>&</sup>lt;sup>4</sup>Battery weight may vary based on manufacturer

<sup>&</sup>lt;sup>5</sup>Includes standard seat