

Scheduled Maintenance



Model: Monster 1200 Monster 821 Diavel MY15-16 Hypermotard / Hyperst	rada I\	/IY13	I-15 a	ind IV	/IY16	
Plate Number: Current km/mi:						
Customer Name: Date of Registration:						
Coloradada Mariatana ana sintana anti-na Olorada Listafan ana tanana da anti-na da anti-	1	15	20	AE	60	_
Scheduled Maintenance intervention Check List for motorcycle equipped with Testastretta 11° 821, Testastretta 11° 939 and Testastretta 11° DS 1200 engine mi. x 1.000	0,6	15 9	30 18	45 27	60 36	Time (months)
Reading of the error memory with DDS 2.0 and check of Software version update on control units	•	•	•	•	•	12
Check the presence of any technical updates and recall campaigns		•	•	•		12
Change engine oil and filter	•	•	•	•	•	12
☐ Clean engine oil intake filter						12
☐ Clean engine oil intake filter (only Monster 821, Hypermotard and Hyperstrada)	•		•		•	
Check and/or adjust valve clearance			•		•	
☐ Change timing belts			•		•	60
☐ Change the spark plugs			•		•	
☐ Change the spark plugs (only Monster 821, Hypermotard and Hyperstrada)		•	•	•	•	
Clean air filter		•		•		
□ Change air filter			•		•	
☐ Check brake and clutch fluid level (only brake fluid for Monster 821, Hypermotard and Hyperstrada)	•	•	•	•	•	12
☐ Change brake and clutch fluid (only brake fluid for Monster 821, Hypermotard and Hyperstrada)						36
☐ Check brake discs and pad wear. Change, if necessary	•	•	•	•	•	12
☐ Check tightening torque of front and rear brake calliper screws and front brake disc screws	•	•	•	•	•	12
Check of tightening of phonic wheel and rear brake disc screws (with removal of the rear wheel shaft, only Diavel)		•	•	•	•	
☐ Check front and rear wheel nuts tightening	•	•	•	•	•	12
Check frame-to-engine fasteners tightening		•	•	•	•	
☐ Check wheel hub bearings			•		•	
Check and lubricate the rear wheel shaft			•		•	
☐ Check the cush drive damper on rear sprocket			•		•	
Check the proper tightening of final drive front and rear sprocket nuts	•	•	•	•	•	12
Check final drive wear (chain, front and rear sprockets) and chain sliding shoes		•	•	•	•	12
☐ Check the final drive chain tension and lubrication	•	•	•	•	•	12
☐ Check steering bearings and lubricate, if necessary			•		•	
☐ Change front fork fluid			•		•	
☐ Change front fork fluid (only Hypermotard and Hyperstrada)				•		
☐ Visual check of front fork and rear shock absorber seals	•	•	•	•	•	12
☐ Check the freedom of movement and tightening of the side stand (if installed)	•	•	•	•	•	12
□ Visual check of the fuel lines		•	•	•	•	12
Check rubbing points, clearance, freedom of movement and positioning of hoses and electric wiring in view	•	•	•	•	•	12
☐ Lubricate the levers at the handlebar and pedal controls		•	•	•	•	12
☐ Change coolant				•		48
☐ Check coolant level and circuit for damage	•	•	•	•	•	12
☐ Check tyres pressure and wear	•	•	•	•	•	12
☐ Check the battery charge level	•	•	•	•	•	12
Check the operation of the safety electrical devices (side stand sensor, front and rear brake switches, engine stop switch, gear/neutral sensor)	•	•	•	•	•	12
☐ Check lights, turn indicators, horn and controls	•	•	•	•	•	12
☐ Reset Service indication through DDS 2.0	•	•	•	•	•	
Final test and road test of the motorcycle, testing safety devices (ex. ABS and DTC), electric fans and idling	•	•	•	•	•	12
☐ Softly clean the motorcycle	•	•	•	•	•	12
☐ Fill out that the service was performed in on-board documentation (Service Booklet)	•	•	•	•	•	12
Tick the box next to the interventions carried out during Scheduled Maintenance						