



Direct Drive Truck Units

A complete line of refrigeration units for a wide variety of vehicle chassis and applications.





CLEAN, EFFICIENT, RELIABLE.

THERMO KING DIRECT DRIVE VEHICLE-POWERED UNITS FOR A WIDE VARIETY OF APPLICATIONS

Every day your business faces new challenges - increasing fuel costs, new idling and noise regulations, food safety, driver turnover - all while you're expected to continue to deliver the freshest product possible to your customers. That's where Thermo King comes in. With a full range of direct-drive units to suit your needs, from straight trucks to delivery vans, flowers to seafood, Thermo King has the temperature control solution for you.

DELIVERING WHAT MATTERS TO YOU:



R-134A REFRIGERANT FOR FRESH APPLICATIONS

- Lower pressure refrigerant means a longer unit lifespan
- More reliable with better temp management for fresh loads

R-404A REFRIGERANT FOR FROZEN APPLICATIONS

- Greater cooling capacity
- Better temp management for frozen loads

- **Low Fuel Consumption and Running Costs** achieved by optimizing performance according to the capacity demand, thereby reducing the fuel consumption of the truck.
- **DSR (Direct Smart Reefer) Controller** delivers optimum temperature control and monitoring.
- **Superior Capacity and Airflow** to ensure superior temperature distribution to protect the product load.
- **SmartPower Electric Standby** capacity is a maximum of 82% of the road capacity at any working conditions for maximum protection of the load at any time.
- **Outstanding Pull-Down Capacity** for improved pull-down and recovery time to guarantee product quality.
- **Ideal for Demanding Conditions** and able to function in ambient temperatures up to 122°F with both R-134a and R-404A versions available for fresh and frozen applications.
- **Low Noise Level** in all operating conditions, particularly in steady state conditions.
- **CARB TRU Exemption** saves you time and money by not having to register units or do expensive compliance upgrades.
- **Backed by the Thermo King Dealer Service Network** with expert service and support at over 200 locations across North America.
- **Multi-Temperature Operation** for transporting combinations of fresh and frozen goods gives you maximum flexibility.



B-100

The B-100 is a compact, all-electric unit that provides outstanding refrigeration capacity for small trucks and vans in fresh applications. The system is powered by the vehicle's battery (minimum 250 amp alternator recommended) and does not require a compressor mounted in the engine compartment or extra refrigerant hoses. The B-100 is controlled by the Thermo King Direct Smart Reefer (DSR) controller, which delivers maximum temperature control and efficiency.

B-100 FEATURES INCLUDE:

- Ultra-thin ceiling mounted evaporator to increase payload space
- Low battery voltage protection
- SmartPower electric standby standard (115 VAC)
- Hermetic refrigeration system
- Lightweight construction
- R-134a refrigerant
- 12VDC
- Backed by Thermo King's world-wide service network



V-200/V-300

The V-200 and V-300 vehicle powered units deliver day-in and day-out cooling performance for small van or compartmental applications. Both systems use an engine-mounted compressor (TK-13 and TK-15 respectively) and are available in MAX configurations for higher capacity needs or frozen goods.

V-200/V-300 FEATURES INCLUDE:

- SmartPower electric standby option (115 or 230 VAC)
- Automatic hot gas defrost
- Optional heating package (hot gas or coolant heat)
- Jet Lube compressor lubrication
- Jet Cool compressor injection cooling (MAX units)
- DSR controller
- R-134a or R-404a (MAX) refrigerants
- 12VDC
- Lightweight construction





V-520RT (Rooftop)



V-520 (Nosemount)



V-520 NOSEMOUNT AND ROOFTOP

The V-520 provides superior cooling performance in two different packages: nosemount and rooftop. The nosemount unit is ideal for medium size box trucks, while the rooftop arrangement is perfect for large vans and body-on-chassis vehicles with reach-in side compartments. Only Thermo King offers a unit with this much capacity in a slim line package (just 6 inches above the roof for non-standby units).

Both units use an engine-mounted TK-16 compressor or optional TK-312 reciprocating compressor. Refrigerant R-404a is available for MAX and SPECTRUM units for frozen and multi-temp applications, while R-134a is available for fresh applications.

V-520 FEATURES INCLUDE:

- SmartPower electric standby option (230 VAC)
- Automatic hot gas defrost
- Optional heating package (hot gas, MAX units)
- Jet Lube compressor lubrication
- Jet Cool compressor injection cooling (MAX units)
- DSR controller
- 12VDC
- 24VDC (non-standby units only)
- Lightweight construction
- Very long life condenser fans



V-800

The V-800 is the largest vehicle-powered system that Thermo King has to offer. The unit provides unparalleled cooling performance, even up to trucks 24' in length. Use the V-800 where large urban transport is needed, but the higher costs of maintaining an extra diesel engine are not.

The V-800 consists of a two-piece, split design for fresh, frozen and deep frozen applications for medium to large trucks. The road compressor is powered by the vehicle's engine and the electric standby compressor is powered by an electric motor located in the unit.

V-800 Series units are equipped with an industry-standard swash plate compressor, which uses a wide range of drive kits for ease of installation.



V-800 FEATURES INCLUDE:

- Highest cooling capacity on the market
- SmartPower electric standby option (230 VAC)
- Automatic hot gas defrost
- Jet Lube compressor lubrication
- Jet Cool compressor injection cooling (MAX units)
- DSR controller
- 12VDC
- 24VDC
- Lightweight construction
- Low-noise operation
- Very long life condenser fans

DSR CONTROLLER

THE LATEST IN MICROPROCESSOR-BASED INTELLIGENT CONTROL

- Advanced control but simple to use
- Flexible, modular and stylish
- Enables error-free control and monitoring of the refrigeration unit from inside the cab



THE DSR IN-CAB DISPLAY

Equipped with the most advanced features to provide best user interface experience, including LCD technology for comfortable exposure and outstanding display conditions and an LED backlight for optimal viewing without additional light. Multiple available functions provide the flexibility to adapt to your specific transport application while guaranteeing optimal temperature control and product integrity while displaying alarm code symbols for quick driver response.

STANDARD FEATURES:

- Automatic start-up to restart unit in case of power interruption, switches between standby and over-the-road operation automatically
- Separate hour meters to record total unit on time, engine compressor run time and electric standby compressor run time
- Simple alarm codes for rapid diagnosis and reduced maintenance costs
- Manual or automatic defrost allowing defrost initiation and termination to be scheduled to suit the application
- Vehicle battery protection with low voltage monitoring, sequential evaporator starts and “soft starting” during unit power-up
- Compressor protection with optional “soft start” feature to increase engine compressor life

PROGRAMMABLE FEATURES:

- Set-point lock prevents the driver modifying a pre-determined temperature
- Door switches shut down the unit when door is opened to help maintain box temperature and protect the load (optional)
- Wintrac, a Windows-based software package, allows configuration parameters to be edited in the field and system values such as voltage, pressure and alarms to be logged and read
- Firmware upgrades can be carried out in the field
- Independent control of two-compartments on SPECTRUM multi-temp units allows compartments to switch on/off independently
- Evacuation mode to pump down the system

THE DSR CONTROL BOARD

- Modular concept, separating the control and power relay boards (VPRS-111)
- Improved reliability, serviceability and component replacement
- Reduced service and maintenance costs



COMPRESSORS

Thermo King vehicle-powered systems use industry-standard swash plate compressors that deliver excellent performance in a compact size. The compressor is sized for the size of the unit and speed of the engine. For increased reliability and performance, the TK-208 and TK-312 reciprocating compressors are also available.

AVAILABLE OPTIONS:

DOOR SWITCH KIT

Reduces load temperature rise and saves fuel when the vehicle doors are opened by turning off the refrigeration system. Unit will automatically restart when doors are closed.

DIN ADAPTOR

The din adaptor box enables the DSR controller to be installed in the vehicle dashboard. The aesthetically-designed box allows the controller to be fitted in any available radio slot.

HOSE COVERS

A highly durable kit providing total protection for hoses and cables while enhancing vehicle appearance. Easily installed on all bodies.










MUFFLER KIT

Purpose-designed kit to eliminate transmission of unit vibration and noise into the driver cab. Provides significant gains in driver comfort.

SNOW COVERS

Designed to protect the unit condenser in extreme conditions. The aerodynamically-designed snow cover prevents the build-up of snow and ice on fan blades, avoiding downtime and additional maintenance costs.

BOX SIZE/TEMPERATURE GUIDE DIRECT DRIVE UNITS*

Temp	 6'	 8'	 10'	 12	 14	 16	 18	 20	 22
35°F -2°C	v-200 or B-100	v-200 or B-100	V-300	V-300 or V-520RT	V-520 or V-520RT	V-520 or V-520RT	V-520 or V-520RT	V-800MAX	V-800MAX
0°F -18°C	V-200MAX	V-300MAX	V-300MAX or V-520RT MAX	V-520 MAX or V-520RT MAX	V-520 MAX or V-520RT MAX	V-520 MAX or V-520RT MAX	V-800MAX	V-800MAX	Contact your Dealer
-20°F -29°C	V-200MAX	V-300MAX or V-520RT MAX	V-300MAX or V-520RT MAX	V-300MAX or V-520RT MAX	V-800MAX	V-800MAX	Contact your Dealer	Contact your Dealer	Contact your Dealer

*Above reference assumes 3" of insulation for 35°F (2°C), 0°F (-18°C) and 4" for -20°F (-29°C); ten door openings per delivery day; box dimensions of 96"W and 96"H on trucks 10' and over in length.

COOLING AND HEATING CAPACITIES DIRECT DRIVE UNITS

Model	Refrigerant	Truck Engine Cooling Capacity-BTU/hr			Electric Standby Cooling Capacity-Btu/hr.			Evap Airflow	Heating-Btu/hr.	
		35°F	0°F	-20°F	35°F	0°F	-20°F	CFM	Engine	Electric
B-100	R-134a	3,600	1,300	----	3,700	1,400	----	400	----	----
V-200	R-134a	5,930	3,410	----	4,700	2,120	----	650	14,400	5,000
V-200 MAX	R-404A	7,160	4,775	3,170	5,250	3,410	2,265	650	14,400	5,000
V-300	R-134a	9,590	4,130	----	6,690	2,425	----	765	14,400	5,000
V-300 MAX	R-404A	10,015	5,835	3,535	5,800	3,790	2,565	765	14,400	5,000
V-520	R-404A	12,200	5,000	----	10,000	3,500	----	1,415	----	----
V-520 RT										
V-520 MAX										
V-520 RT MAX										
V-520 SPECTRUM										
V-520 RT SPECTRUM	15,500	8,200	5,000	10,400	6,600	3,500	1,415	14,000	8,000	
V-800	R-134a	16,400	6,175	----	16,500	7,700	----	1,576	----	----
V-800 MAX	R-404A	20,500	9,500	6,000	21,000	11,000	6,200	1,576	----	----



Ingersoll Rand's Climate Solutions sector delivers energy-efficient HVACR solutions for customers globally. Its world class brands include Thermo King, the leader in transport temperature control and Trane, a provider of energy efficient heating, ventilating and air conditioning systems, building and contracting services, parts support and advanced controls for commercial buildings and homes.

Distributed by: