



SERVICE BULLETIN

February 2021

Subject: High Altitude / Sea Level Specifications

No. **2022-1**

YEAR	MODEL
2022	All Ski-Doo

TABLE OF CONTENTS

	Page		Page
GENERAL INFORMATION	4	Drive Pulley.....	10
Previous Model Year Vehicles	4	Driven Pulley	10
Table Format	4	MX Z X-RS™ 600R E-TEC	11
Sea Level Calibration Kit (CAN/USA only) ...	4	Drive Pulley.....	11
MX Z™ SPORT 600 EFI /RENEGADE SPORT 600 EFI	5	Driven Pulley	11
Drive Pulley.....	5	RENEGADE™ ADRENALINE™ 600R E-TEC /RENEGADE ENDURO 600R E-TEC /RENEGADE X 600R E-TEC	12
Driven Pulley	5	Drive Pulley.....	12
BACKCOUNTRY SPORT 600 EFI	6	Driven Pulley	12
Drive Pulley.....	6	SUMMIT SP 146" AND 154" 600R E-TEC (CAN/USA)	13
Driven Pulley	6	Drive Pulley.....	13
EXPEDITION™ SPORT 600 EFI /SKANDIC SPORT 600 EFI /SKANDIC WT 600 EFI /TUNDRA SPORT 600 EFI /TUNDRA LT 600 EFI	7	Driven Pulley	13
Drive Pulley.....	7	Vehicle Calibration	13
Driven Pulley	7	BACKCOUNTRY 600R E-TEC /SUMMIT SP 146" AND 154" 600R E-TEC (EUROPE) .	14
EXPEDITION LE 600R E-TEC /EXPEDITION SE 600R E-TEC /SKANDIC WT 600R E-TEC	8	Drive Pulley.....	14
Drive Pulley.....	8	Driven Pulley	14
Driven Pulley	8	Vehicle Calibration	14
EXPEDITION SWT 600R E-TEC /SKANDIC SWT 600R E-TEC	9	EXPEDITION Xtreme 850 E-TEC	15
Drive Pulley.....	9	Drive Pulley.....	15
Driven Pulley	9	Driven Pulley	15
MX Z™ TNT 600R E-TEC /MX Z X™ 600R E-TEC	10	FREERIDE 146" 850 E-TEC SEA-LEVEL (CAN/USA)	16
		Drive Pulley.....	16
		Driven Pulley	16
		Vehicle Calibration	16

Chaincase Gears.....	16
FREERIDE 146" 850 E-TEC SEA-LEVEL (EUR) /SUMMIT 146" 850 E-TEC SEA-LEVEL (EUR)	17
Drive Pulley.....	17
Driven Pulley	17
Vehicle Calibration	17
Chaincase Gears.....	17
FREERIDE 154" AND 165" 850 E-TEC SEA-LEVEL (CAN/USA) /SUMMIT 154" AND 165" 850 E-TEC SEA-LEVEL (CAN/USA)	18
Drive Pulley.....	18
Driven Pulley	18
Vehicle Calibration	18
Chaincase Gears.....	18
FREERIDE 154" AND 165" 850 E-TEC SEA-LEVEL (EUR) /SUMMIT 154" AND 165" 850 E-TEC SEA-LEVEL (EUR)	20
Drive Pulley.....	20
Driven Pulley	20
Vehicle Calibration	20
Chaincase Gears.....	20
SUMMIT 146" 850 E-TEC HIGH ALTITUDE	21
Drive Pulley.....	21
Driven Pulley	21
Vehicle Calibration	21
Chaincase Gears.....	21
FREERIDE 154" AND 165" 850 E-TEC HIGH ALTITUDE /SUMMIT 154" AND 165" 850 E-TEC HIGH ALTITUDE.....	23
Drive Pulley.....	23
Driven Pulley	23
Vehicle Calibration	23
Chaincase Gears.....	23
SUMMIT 175" 850 E-TEC HIGH ALTITUDE	25
Drive Pulley.....	25
Driven Pulley	25
Vehicle Calibration	25
Chaincase Gears.....	25
FREERIDE 154" AND 165" 850 E-TEC TURBO SEA LEVEL (EUR) /SUMMIT 154" AND 165" 850 E-TEC TURBO SEA LEVEL (EUR)	27
Drive Pulley.....	27
Driven Pulley	27
Vehicle Calibration	27

Chaincase Gears.....	28
FREERIDE 154" AND 165" 850 E-TEC TURBO HIGH ALTITUDE (CAN/USA) /SUMMIT 154", 165" AND 175" 850 E-TEC TURBO HIGH ALTITUDE (CAN/USA AND ASIA)	29
Drive Pulley.....	29
Driven Pulley	29
Vehicle Calibration	29
Chaincase Gears.....	30
MX Z TNT 850 E-TEC /MX Z X 850 E-TEC /MX Z X-RS 850 E-TEC.....	31
Drive Pulley.....	31
Driven Pulley	31
RENEGADE ADRENALINE 850 E-TEC /RENEGADE X 850 E-TEC /RENEGADE X-RS 850 E-TEC /RENEGADE ENDURO 850 E-TEC	32
Drive Pulley.....	32
Driven Pulley	32
BACKCOUNTRY 850 E-TEC /BACKCOUNTRY X 850 E-TEC /BACKCOUNTRY X-RS 850 E-TEC(Track with profile of 40 mm (1.6 in)).....	33
Drive Pulley.....	33
Driven Pulley	33
Vehicle Calibration	33
Chaincase Gears.....	33
BACKCOUNTRY X 850 E-TEC /BACKCOUNTRY X-RS 850 E-TEC (CAN/USA)(Track with profile of 50 mm (2 in) and 63 mm (2-1/2 in)).....	35
Drive Pulley.....	35
Driven Pulley	35
Vehicle Calibration	35
Chaincase Gears.....	36
BACKCOUNTRY X-RS 850 E-TEC (EUR)	37
Drive Pulley.....	37
Driven Pulley	37
Vehicle Calibration	37
Chaincase Gears.....	37
TUNDRA SPORT 600 ACE /TUNDRA LT 600 ACE.....	38
Drive Pulley.....	38
Driven Pulley	38
RENEGADE SPORT 600 ACE /GRAND TOURING SPORT 600 ACE.....	39
Drive Pulley.....	39
Driven Pulley	39

EXPEDITION SPORT 600 ACE	40
Drive Pulley.....	40
Driven Pulley	40
SKANDIC WT 600 ACE	41
Drive Pulley.....	41
Driven Pulley	41
EXPEDITION LE / SE 900 ACE.....	42
Drive Pulley.....	42
Driven Pulley	42
GRAND TOURING SPORT 900 ACE /GRAND TOURING LTD 900 ACE /RENEGADE ADRENALINE 900 ACE /RENEGADE ENDURO 900 ACE	43
Drive Pulley.....	43
Driven Pulley	43
EXPEDITION SPORT 900 ACE	44
Drive Pulley.....	44
Driven Pulley	44
SKANDIC WT 900 ACE	45
Drive Pulley.....	45
Driven Pulley	45
EXPEDITION SWT 900 ACE /SKANDIC SWT 900 ACE	46
Drive Pulley.....	46
Driven Pulley	46
EXPEDITION LE / SE 900 ACE TURBO .	47
Drive Pulley.....	47
Driven Pulley	47
EXPEDITION SWT 900 ACE TURBO	48
Drive Pulley.....	48
Driven Pulley	48
GRAND TOURING LTD 900 ACE TURBO.....	49
Drive Pulley.....	49
Driven Pulley	49
RENEGADE X 900 ACE TURBO/RENE- GADE X-RS 900 ACE TURBO/RENEGADE ADRENALINE 900 ACE TURBO/RENE- GADE ENDURO 900 ACE TURBO.....	50
Drive Pulley.....	50
Driven Pulley	50
MACH Z 900 ACE TURBO	51
Drive Pulley.....	51
Driven Pulley	51
OPTIONAL DRIVE PULLEY SPRING RATES AND SPECIFICATIONS	52

eDrive II (900 ACE) and eDrive II LC (600 ACE)	52
---	----

GENERAL INFORMATION

Previous Model Year Vehicles

This bulletin supplies all the information required to modify current year vehicles for high altitude and/or sea level riding.

MODEL YEAR	LATEST REVISION OF BULLETIN NO.
2022	2022-1
2021	2021-1
2020	2020-1
2019	2019-2
2018	2018-5

NOTE: Throughout this entire document, shaded areas give factory settings (that could apply through different altitudes) while N/A stands for "not applicable".

NOTICE The following modifications and adjustments apply for high altitude operation as well as sea level operation.

PARTS AND LABOR COST ARE NOT COVERED BY BRP LIMITED WARRANTY.

Table Format

The shaded portions of the table indicate factory settings.

ALTITUDE	
Parts to be modified	Recommended Adjustment

Sea Level Calibration Kit (CAN/USA only)

When the high altitude calibration must be modified to sea level calibration on Freeride™ and Summit™ models (146" and up), the following kit may be used. This kit include all required parts to set-up the vehicle.

MODEL	PART NUMBER
Summit 600R E-TEC	
146" and 154"	860202145
Freeride and Summit 850 E-TEC except turbo	
146", 154", 165", and 175"	860201905

Kit Description

SEA LEVEL CALIBRATION KIT (P/N 860201905)			
DESCRIPTION		PART NUMBER	QTY
Drive pulley	Ramp 990	417224326	3
	Weight	417224507	3
	Pivot 38 mm / 16,7 g	417224222	3
	Spring (Blue/Yellow)	417224015	1
	M14 Conical spring washer	250200144	1
Driven pulley	Spring (Black)	417127039	1

SEA LEVEL CALIBRATION KIT (P/N 860202145)			
DESCRIPTION		PART NUMBER	QTY
Drive pulley	Spring (Purple/White)	417224167	1
	Ramp 901	417224626	3
	Pivot 38 mm/16,7 g	417224222	3
	M14 Conical spring washer	250200144	1
Driven pulley	Spring (black)	417127039	1

MX Z™ SPORT 600 EFI / RENEGADE SPORT 600 EFI

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Blue/Blue (P/N 417224013)			Purple/Blue (P/N 417224165)	
Ramp		886 (P/N 417224688)			972 (P/N 417224268) ¹	
Calibration cam position		N/A			4	5
Mass		N/A			26 mm/13,1 g (P/N 417224220)	
Engagement RPM ± 100		3200			3500	
Maximum RPM ± 100		7500				

¹Parts required to complete the clicker assembly: Cam (P/N 417224113), mass (P/N 417224220), levers (P/N 417224114) and (P/N 417224086). Adjust calibration cam as per table

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Green (P/N 417127137)				
Spring tension Kg ± 0.7 (lb ± 1.5)		N/A				
Cam angle (degrees)		44° (P/N 417127367)				

BACKCOUNTRY SPORT 600 EFI

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)			Purple/Blue (P/N 417224165)		
Ramp	886 (P/N 417224688)			972 (P/N 417224268) ¹		
Calibration cam position	N/A			4	5	
Mass	N/A			26 mm/13,1 g (P/N 417224220)		
Engagement RPM \pm 100	3200			3500		
Maximum RPM \pm 100	7500					
¹ Parts required to complete the clicker assembly: Cam (P/N 417224113), mass (P/N 417224220), levers (P/N 417224114) and (P/N 417224086). Adjust calibration cam as per table						

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

**EXPEDITION™ SPORT 600 EFI /
 SKANDIC SPORT 600 EFI /
 SKANDIC WT 600 EFI /
 TUNDRA SPORT 600 EFI /
 TUNDRA LT 600 EFI**

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Yellow/Yellow (P/N 417224171)			Blue/Blue (P/N 417224013)		
Ramp	887 (P/N 417224690)			972 (P/N 417224268) ¹		
Calibration cam position	N/A			4	5	
Mass	N/A			26 mm/13,1 g (P/N 417224220)		
Engagement RPM ± 100	2300			3100		
Maximum RPM ± 100	7500					
¹ Parts required to complete the clicker assembly: Cam (P/N 417224113), mass (P/N 417224220), levers (P/N 417224114) and (P/N 417224086). Adjust calibration cam as per table						

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

EXPEDITION LE 600R E-TEC / EXPEDITION SE 600R E-TEC / SKANDIC WT 600R E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Yellow/Blue (P/N 417224172)					
Ramp	971 (P/N 417224266)			972 (P/N 417224268)		
Calibration cam position	3	4	5	3	4	5
Mass	26 mm/13,1 g (P/N 417224220)					
Engagement RPM \pm 100	3400			2900		
Maximum RPM \pm 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

EXPEDITION SWT 600R E-TEC / SKANDIC SWT 600R E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Yellow/Blue (P/N 417227172)					
Ramp	971 (P/N 417224266)			972 (P/N 417224268)		
Calibration cam position	4	5		4	5	
Mass	38 mm/16,7 g (P/N 417224222) + 2 mm (P/N 417224363)			38 mm/16,7 g (P/N 417224222)		
Engagement RPM \pm 100	3400			2800		
Maximum RPM \pm 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

MX Z™ TNT 600R E-TEC / MX Z X™ 600R E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Blue (P/N 417224013)			Purple/Purple (P/N 417224166)		
Ramp	901 (P/N 417224626)			967 (P/N 417224225)		
Calibration cam position	3	4	5	4		5
Mass	33 mm/15,2 g (P/N 417224221)			26 mm/13,1 g (P/N 417224220)		
Engagement RPM ± 100	300			4000		
Maximum RPM ± 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	44° (P/N 417127367)					

MX Z X-RS™ 600R E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Blue (P/N 417224013)			Green/Purple (P/N 417224014)		
Ramp	901 (P/N 417224626)			967 (P/N 417224225)		
Calibration cam position	3	4	5	4		5
Mass	33 mm/15,2 g (P/N 417224221)			26 mm/13,1 g (P/N 417224220)		
Engagement RPM ± 100	3400			4000		
Maximum RPM ± 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	44° (P/N 417127367)					

RENEGADE™ ADRENALINE™ 600R E-TEC / RENEGADE ENDURO 600R E-TEC / RENEGADE X 600R E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Blue (P/N 417224013)			Purple/Purple (P/N 417224166)		
Ramp	901 (P/N 417224626)			967 (P/N 417224225)		
Calibration cam position	3	4	5	4		5
Mass	33 mm/15,2 g (P/N 417224221)			26 mm/13,1 g (P/N 417224220)		
Engagement RPM \pm 100	3400			4000		
Maximum RPM \pm 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° (P/N 417127367)			43° - 47° (P/N 417127371)		

SUMMIT SP 146" AND 154" 600R E-TEC (CAN/USA)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Purple/White (P/N 417224167)			Blue/Purple (P/N 417224168)		
Ramp	901 (P/N 417224626)			997 (P/N 417224430)		
Calibration cam position	3	4	5	3	4	5
Mass	38 mm/16,7 g (P/N 417224222)			33 mm/15,2 g (P/N 417224221)		
Engagement RPM \pm 100	3400					
Maximum RPM \pm 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)			Blue (P/N 417127118)		
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	46° - 42° XTI (P/N 417127426)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Sea Level Calibration Kit

MODEL	PART NUMBER
146"	860202145

BACKCOUNTRY 600R E-TEC / SUMMIT SP 146" AND 154" 600R E-TEC (EUROPE)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Purple/White (P/N 417224167)			Blue/Purple (P/N 417224168)		
Ramp	901 (P/N 417224626)			997 (P/N 417224430)		
Calibration cam position	3	4	5	3	4	5
Mass	38 mm/16,7 g (P/N 417224222)			33 mm/15,2 g (P/N 417224221)		
Engagement RPM \pm 100	3400					
Maximum RPM \pm 100	8100					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)			Blue (P/N 417127118)		
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	46° - 42° XTI (P/N 417127426)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

EXPEDITION Xtreme 850 E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)					
Ramp	982 (P/N 417224575)			904 (P/N 417224646)		
Calibration cam position	3	4	2	3	4	5
Mass	38 mm/ 16,7g (P/N 417224222) + 2 mm (P/N 417224363)			26 mm/13,1 g (P/N 417224220)		
Engagement RPM \pm 100	3800			2900		
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42° - 40° (P/N 417127430)					

FREERIDE 146" 850 E-TEC SEA-LEVEL (CAN/USA)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	4	5	3	4	5	
Mass	38 mm/ 16,7g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3800			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42°-38° XTI (P/N 417127693)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

146" MODELS						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504153910)					
Lower gear	49 (P/N 504152581)					
Chain	114 (P/N 504153393)					

FREERIDE 146" 850 E-TEC SEA-LEVEL (EUR) / SUMMIT 146" 850 E-TEC SEA-LEVEL (EUR)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	3	4	3	4	5	
Mass	38 mm/ 16,7g (P/N 417224222)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3800			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44°-42° XTI (P/N 417127825)		40° XTI (P/N 417127672)			

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

146" MODELS						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504153910)					
Lower gear	51 (P/N 504154110)					
Chain	116 (P/N 504153397)					

FREERIDE 154" AND 165" 850 E-TEC SEA-LEVEL (CAN/USA) / SUMMIT 154" AND 165" 850 E-TEC SEA-LEVEL (CAN/USA)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	4	5	3	4	5	
Mass	38 mm/16,7 g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3800			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

154" MODELS						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M FT
Upper gear		21 (P/N 504153910)				
Lower gear		51 (P/N 504152971)				
Chain		116 (P/N 504153397)				

165" MODELS						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M FT
Upper gear	21 (P/N 504153910)					
Lower gear	53 (P/N 504153998)					
Chain	116 (P/N 504153397)					

FREERIDE 154" AND 165" 850 E-TEC SEA-LEVEL (EUR) / SUMMIT 154" AND 165" 850 E-TEC SEA-LEVEL (EUR)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	3	4	3	4	5	
Mass	38 mm/16,7 g (P/N 417224222)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM ± 100	3300		3800			
Maximum RPM ± 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)		Blue (P/N 417127118)			
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	44°-42° XTI (417127825)		40° XTI (P/N 417127672)			

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

154" AND 165" MODELS						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M FT
Upper gear		21 (P/N 504153910)				
Lower gear		53 (P/N 504153998)				
Chain		116 (P/N 504153397)				

SUMMIT 146" 850 E-TEC HIGH ALTITUDE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	4	5	3	4	5	
Mass	38 mm/ 16,7g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3600			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42°-38° XTI (P/N 417127693)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

146" MODELS						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504153910)					
Lower gear	49 (P/N 504152581)					
Chain	114 (P/N 504153393)					

Sea Level Calibration Kit

MODEL	PART NUMBER
146"	860201905

FREERIDE 154" AND 165" 850 E-TEC HIGH ALTITUDE / SUMMIT 154" AND 165" 850 E-TEC HIGH ALTITUDE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	4	5	3	4	5	
Mass	38 mm/ 16,7g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3600			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

154" MODELS						
	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504153910)					
Lower gear	51 (P/N 504152971)					
Chain	116 (P/N 504153397)					

165" MODELS						
SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)	
Upper gear	21 (P/N 504153910)					
Lower gear	53 (P/N 504153998)					
Chain	116 (P/N 504153397)					

Sea Level Calibration Kit

MODEL	PART NUMBER
154" and 165"	860201905

Summit 154" and 165" 850 E-TEC Gear Ratio and Application

NOTE: Summit are built for deep snow conditions and should never be used in marginal or hard pack snow conditions. Going to higher ratios could lead to reduced belt life and track delamination.

GEAR RATIO	APPLICATION	PRO'S	CON'S
21/51	Best all around gear ratio	Reference	116 km/h max speed. Rev limiter can turn on
21/53	Deep snow	Better belt life	111 km/h max speed. Rev limiter can turn on

SUMMIT 175" 850 E-TEC HIGH ALTITUDE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Purple/White (P/N 417224167)			
Ramp	990 (P/N 417224326)		965 (P/N 417224141)			
Calibration cam position	4	5	3	4	5	
Mass	38 mm/ 16,7g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/15,2 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3900			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

175" MODELS						
	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504153910)					
Lower gear	53 (P/N 504153998)					
Chain	116 (P/N 504153397)					

Sea Level Calibration Kit

MODEL	PART NUMBER
175"	860201905

FREERIDE 154" AND 165" 850 E-TEC TURBO SEA LEVEL (EUR) / SUMMIT 154" AND 165" 850 E-TEC TURBO SEA LEVEL (EUR)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)	Blue/Purple (P/N 417224168)				
Ramp	951 (P/N 417224038)	994 (P/N 417224758)				903 (P/N 417224642)
Calibration cam position	3	1				5 (154") 4 (165")
Mass	33 mm/15,2 g (P/N 417224221)	33 mm/15,2 g (P/N 417224221) + 3 mm (P/N 417224364)			33 mm /15,2 g (P/N 417 224221)	38 mm/ 16,7g (P/N 417224 222) + 7 mm (P/N 417224366)
Engagement RPM \pm 100	3800					
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	41°-45° XTI (P/N 417127714)	40° XTI (P/N 417127672)				

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

FREERIDE 165" AND SUMMIT 154" AND 165" MODELS						
	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504154188)					
Lower gear	53 (P/N 504154167)					
Chain	116 (P/N 504153759)					

FREERIDE 154" MODELS						
	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504154188)					
Lower gear	51 (P/N 504154183)					
Chain	116 (P/N 504153759)					

Gear Ratio and Application

NOTE: Summit and Freeride are built for deep snow conditions and should never be used in marginal or hard pack snow conditions. Going to higher ratios could lead to reduced belt life and track delamination.

GEAR RATIO	APPLICATION	PRO'S	CON'S
21/51	Best all around gear ratio	Reference	116 km/h max speed. Rev limiter can turn on
21/53	Deep snow	Better belt life	111 km/h max speed. Rev limiter can turn on

FREERIDE 154" AND 165" 850 E-TEC TURBO HIGH ALTITUDE (CAN/USA) / SUMMIT 154", 165" AND 175" 850 E-TEC TURBO HIGH ALTITUDE (CAN/USA AND ASIA)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Purple (P/N 417224168)					
Ramp	994 (P/N 417224758)					903 (P/N 417224642)
Calibration cam position	3	1			5 (154") 4 (165" and 175")	
Mass	38H mm/ 19,8g (P/N 417224806) + 9 mm (P/N 417224507)	33 mm/15,2 g (P/N 417224221) + 3 mm (P/N 417224364)			33 mm /15,2 g (P/N 417 224221)	38 mm/ 16,7g (P/N 417224 222) + 7 mm (P/N 417224366)
Engagement RPM \pm 100	3800					
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap	4	3		2		

Chaincase Gears

FREERIDE 154" MODELS						
	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504154188)					
Lower gear	51 (P/N 504154183)					
Chain	116 (P/N 504153759)					

165" AND 175" MODELS						
	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504154188)					
Lower gear	53 (P/N 504154167)					
Chain	116 (P/N 504153759)					

Gear Ratio and Application

NOTE: Summit and Freeride are built for deep snow conditions and should never be used in marginal or hard pack snow conditions. Going to higher ratios could lead to reduced belt life and track delamination.

GEAR RATIO	APPLICATION	PRO'S	CON'S
21/51	Best all around gear ratio	Reference	116 km/h max speed. Rev limiter can turn on
21/53	Deep snow	Better belt life	111 km/h max speed. Rev limiter can turn on

MX Z TNT 850 E-TEC / MX Z X 850 E-TEC / MX Z X-RS 850 E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Blue (P/N 417224013)		Blue/Yellow (P/N 417224015)			
Ramp	968 (P/N 417224227)		967 (P/N 417224225)			
Calibration cam position	3	4	2	3	4	5
Mass	38 mm/ 16,7g (P/N 417224222)					
Engagement RPM \pm 100	3200		4000			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	45° - 42° (P/N 417127534)					

RENEGADE ADRENALINE 850 E-TEC / RENEGADE X 850 E-TEC / RENEGADE X-RS 850 E-TEC / RENEGADE ENDURO 850 E-TEC

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Yellow/Blue (P/N 417224172)		Yellow/Yellow (P/N 417224171)			
Ramp	968 (P/N 417224227)		967 (P/N 417224225)			
Calibration cam position	3	4	2	3	4	5
Mass	38 mm/ 16,7g (P/N 417224222)					
Engagement RPM ± 100	2900		3400			
Maximum RPM ± 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	44° - 42° (P/N 417127325)					

BACKCOUNTRY 850 E-TEC / BACKCOUNTRY X 850 E-TEC / BACKCOUNTRY X-RS 850 E-TEC (Track with profile of 40 mm (1.6 in))

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		995 (P/N 417224450)			
Calibration cam position	4	5	3		4	
Mass	38 mm/16,7 g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/18.8 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM \pm 100	3300		3800			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	42° - 38° XTI (P/N 417127693)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

WITH 1.6" PROFILE TRACK						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Upper gear	21 (P/N 504153910)					
Lower gear	45 (P/N 504152593)					
Chain	112 (P/N 504153268)					

BACKCOUNTRY X 850 E-TEC / BACKCOUNTRY X-RS 850 E-TEC (CAN/USA) (Track with profile of 50 mm (2 in) and 63 mm (2-1/2 in))

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		995 (P/N 417224450)			
Calibration cam position	4	5	4			5
Mass	38 mm/16,7 g (P/N 417224222) + 9 mm (P/N 417224507)		33 mm/18.8 g (P/N 417224221)		26 mm/13,1 g (P/N 417224220)	
Engagement RPM ± 100	3300		3800			
Maximum RPM ± 100	7900					

Driven Pulley

146" MODELS						
	Sea level 0 m (0 FT)	600 m (2000 FT)	1200 m (4000 FT)	1800 m (6000 FT)	2400 m (8000 FT)	3000 m (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	42° - 38° XTI (P/N 417127693)					

154" MODELS						
	Sea level 0 m (0 FT)	600 m (2000 FT)	1200 m (4000 FT)	1800 m (6000 FT)	2400 m (8000 FT)	3000 m (10000 FT)
Spring	Black (P/N 417127039)		Blue (P/N 417127118)			
Spring tension Kg ± 0.7 (lb ± 1.5)	N/A					
Cam angle (degrees)	40° XTI (P/N 417127672)					

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

WITH 2" PROFILE TRACK						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M FT
Upper gear	23 (P/N 504091000)					
Lower gear	51 (P/N 504152971)					
Chain	116 (P/N 504153397)					

WITH 2.5" PROFILE TRACK						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M FT
Upper gear	21 (P/N 504153910)					
Lower gear	51 (P/N 504152971)					
Chain	116 (P/N 504153397)					

BACKCOUNTRY X-RS 850 E-TEC (EUR)

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Yellow (P/N 417224015)		Blue/Purple (P/N 417224168)			
Ramp	990 (P/N 417224326)		995 (P/N 417224450)			
Calibration cam position	3	4	4		5	
Mass	38 mm/16,7 g (P/N 417224222)		33 mm/18.8 g (P/N 417224221)	26 mm/13,1 g (P/N 417224220)		
Engagement RPM \pm 100	3300		3800			
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)		Blue (P/N 417127118)			
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	44° - 42° XTI (P/N 417127825)		42° - 38° XTI (P/N 417127693)			

Vehicle Calibration

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Stopper Strap		4		3		2

Chaincase Gears

WITH 2" AND 2.5" PROFILE TRACK						
	Sea level 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M FT
Upper gear	21 (P/N 504153910)					
Lower gear	51 (P/N 504152971)					
Chain	116 (P/N 504153397)					

TUNDRA SPORT 600 ACE / TUNDRA LT 600 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Red (P/N 417223745)	Red/Yellow (P/N 417 223748)		Red/White (P/N 417223747)	Red/Red (P/N 417 223745)
Ramp		716 (P/N 417223508)		725 (P/N 417223601)		
Ramp quantity		6				
Engagement RPM \pm 100		2200				
Maximum RPM \pm 100		7300				

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red (P/N 417127467)				
Spring tension Kg \pm 0.7 (lb \pm 1.5)		7.3 kgf (16.1 lbf) (1-C)				
Cam angle (degrees)		41°-45° (P/N 417127747)				

RENEGADE SPORT 600 ACE / GRAND TOURING SPORT 600 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Red/Red (P/N 417 223745)	Red/Yellow (P/N 417 223748)	Red/Orange (P/N 417 223749)	Red/White (P/N 417223747)		Red/Red (P/N 417 223745)
Ramp	715 (P/N 417223510)			725 (P/N 417223601)		
Ramp quantity	6					
Engagement RPM \pm 100	2200					
Maximum RPM \pm 100	7300					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Red/Red (P/N 417127467)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	7.3 kgf (16.1 lbf) (1-C)					
Cam angle (degrees)	41°-45° (P/N 417127747)					

EXPEDITION SPORT 600 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Red (P/N 417223745)	Red/Yellow (P/N 417 223748)	Red/White (P/N 417223747)		Red/Red (P/N 417 223745)
Ramp		716 (P/N 417223508)		725 (P/N 417223601)		
Ramp quantity		6				
Engagement RPM \pm 100		2200				
Maximum RPM \pm 100		7300				

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red (P/N 417127467)				
Spring tension Kg \pm 0.7 (lb \pm 1.5)		7.3 kgf (16.1 lbf) (1-C)				
Cam angle (degrees)		41°-45° (P/N 417127747)				

SKANDIC WT 600 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Red (P/N 417223745)	Red/White (P/N 417 223747)	Red/Red (P/N 417 223745)	Red/Yellow (P/N 417 223748)	Red/Orange (P/N 417 223749)
Ramp		716 (P/N 417223508)	725 (P/N 417223601)			
Ramp quantity		6				
Engagement RPM \pm 100		2200				
Maximum RPM \pm 100		7300				

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red (P/N 417127467344)				
Spring tension Kg \pm 0.7 (lb \pm 1.5)		7.3 kgf (16.1 lbf) (1-C)				
Cam angle (degrees)		41°-45° (P/N 417127747)				

EXPEDITION LE / SE 900 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Blue (P/N 417224330)		Yellow/Yellow (P/N 417224171)		Blue/Blue (P/N 417224013)
Ramp		882 (P/N 417224495)		895 (P/N 417224256)		
Engagement RPM ± 100		2200		2800		3200
Maximum RPM ± 100		7250				

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Beige2 (P/N 417127242)				
Spring tension Kg ± 0.7 (lb ± 1.5)		7.0 kg (15.4 lb) (2-E)				
Cam angle (degrees)		42° (P/N 417127420)				

**GRAND TOURING SPORT 900 ACE /
GRAND TOURING LTD 900 ACE /
RENEGADE ADRENALINE 900 ACE /
RENEGADE ENDURO 900 ACE**

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)	
Spring		Red/Blue (P/N 417224330)				Blue/Purple (P/N 417224168)	
Ramp		826 (P/N 417224370)		895 (P/N 417224256)			
Engagement RPM ± 100		2200		2400		2600	
Maximum RPM ± 100		7250					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)	
Spring		Red (P/N 417127467)					
Spring tension Kg ± 0.7 (lb ± 1.5)		7.3 kg - 6.6 kg (16.1 lb - 14.6 lb)					
Cam angle (degrees)		44° - 40° (P/N 417127476)					

EXPEDITION SPORT 900 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Red/Blue (P/N 417224330)				Blue/Purple (P/N 417224168)	
Ramp	882 (P/N 417224495)		895 (P/N 417224256)			
Engagement RPM \pm 100	2200		2400		2600	
Maximum RPM \pm 100	7300					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Beige2 (P/N 417127242)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	7.0 kg (15.4 lb) (2-E)					
Cam angle (degrees)	42° (P/N 417127420)					

SKANDIC WT 900 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Blue (P/N 417224330)		Yellow/Yellow (P/N 417224171)		Blue/Blue (P/N 417224013)
Ramp		882 (P/N 417224495)		895 (P/N 417224256)		
Engagement RPM \pm 100		2200		2800		3200
Maximum RPM \pm 100		7300				

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Red (P/N 417127467)				
Spring tension Kg \pm 0.7 (lb \pm 1.5)		7.0 kg (15.4 lb) (2-E)				
Cam angle (degrees)		42° - A (P/N 417127420)				

EXPEDITION SWT 900 ACE / SKANDIC SWT 900 ACE

Drive Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Yellow (P/N 417224329)		Yellow/Yellow (P/N 417224171)		Blue/Blue (P/N 417224013)
Ramp		882 (P/N 417224495)		895 (P/N 417224256)		
Engagement RPM \pm 100		2200		2800		3200
Maximum RPM \pm 100		7300				

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring		Red/Red (P/N 417127467)				
Spring tension Kg \pm 0.7 (lb \pm 1.5)		7.0 kg - 6.4 kg (15.4 lb - 14.1 lb) (2-E)				
Cam angle (degrees)		40° (P/N 417127411)				

EXPEDITION LE / SE 900 ACE TURBO

Drive Pulley

NOTE: The factory calibration is suitable for all altitude. The turbocharger compensates for the lack of oxygen at high altitude.

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Red/Yellow (P/N 417224329)					
Ramp	880 (P/N 417224290)					
Engagement RPM \pm 100	2200					
Maximum RPM \pm 100	7300					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue (P/N 417127118)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 40° (P/N 417127756)					

EXPEDITION SWT 900 ACE TURBO

Drive Pulley

NOTE: The factory calibration is suitable for all altitude. The turbocharger compensates for the lack of oxygen at high altitude.

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue/Purple (P/N 417224168)					
Ramp	880 (P/N 417224290)					
Engagement RPM \pm 100	2300					
Maximum RPM \pm 100	7300					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Blue (P/N 417127118)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 40° (P/N 417127756)					

GRAND TOURING LTD 900 ACE TURBO

Drive Pulley

NOTE: The factory calibration is suitable for all altitude. The turbocharger compensates for the lack of oxygen at high altitude.

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Red/Yellow(P/N 417224329)					
Ramp	880 (P/N 417224290)					
Engagement RPM \pm 100	2700					
Maximum RPM \pm 100	7400 (Turbo) 7900 (Turbo R)					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 40° (P/N 417127756)					

RENEGADE X 900 ACE TURBO/ RENEGADE X-RS 900 ACE TURBO/ RENEGADE ADRENALINE 900 ACE TURBO/ RENEGADE ENDURO 900 ACE TURBO

Drive Pulley

NOTE: The factory calibration is suitable for all altitude. The turbocharger compensates for the lack of oxygen at high altitude.

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Purple/Blue (P/N 417224165)					
Ramp	880 (P/N 417224290)					
Engagement RPM \pm 100	2700					
Maximum RPM \pm 100	7400 (Turbo) 7900 (Turbo R)					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 40° (P/N 417127756)					

MACH Z 900 ACE TURBO

Drive Pulley

NOTE: The factory calibration is suitable for all altitude. The turbocharger compensates for the lack of oxygen at high altitude.


	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Purple/Blue (P/N 417224165)					
Ramp	897 (P/N 417224633)					
Engagement RPM \pm 100	3200					
Maximum RPM \pm 100	7900					

Driven Pulley

	SEA LEVEL 0 M (0 FT)	600 M (2000 FT)	1200 M (4000 FT)	1800 M (6000 FT)	2400 M (8000 FT)	3000 M (10000 FT)
Spring	Green (P/N 417127137)					
Spring tension Kg \pm 0.7 (lb \pm 1.5)	N/A					
Cam angle (degrees)	47° - 40° (P/N 417127756)					

OPTIONAL DRIVE PULLEY SPRING RATES AND SPECIFICATIONS

The springs for TRA pulleys can not be installed on eDrive II or eDrive II LC.



TYPICAL - COLOR CODE
 1. 1st color
 2. 2nd color

eDrive II (900 ACE) and eDrive II LC (600 ACE)

SPRING SPECIFICATIONS							
PART NUMBER	WIRE DIA.	FREE LENGHT	LOAD ± 10% WHEN "A" = 60.6 MM		LOAD ± 10% WHEN "A" = 28 MM		COLOR CODE
	MM		N	LBS	N	LBS	
417223745	4.50	97.9	356	80	667	150	Red / Red
417223747	4.30	108.0	356	80	600	135	Red / White
417223748	4.80	87.3	355	80	789	177	Red / Yellow
417223749	4.80	84.3	355	80	845	190	Red / Orange
417223750	5.0	80.5	355	80	934	210	Red / Green
417224084	4.50	105.4	489	110	845	190	Yellow / Pink
417224085	4.30	120.0	446	100	690	155	Yellow / Blue