

# Bandit Model 2250XP Stump Grinder



Bandit has taken stump grinding to a whole new level with the Model 2250XP beltless stump grinder. This revolutionary machine uses a hydrostatic motor to directly power the cutter wheel, eliminating all the belts, shafts and the many pulleys and bearings that typically require regular adjustment and replacement. With a Bandit hydrostatic stump grinder it's not uncommon to see maintenance costs drop by 30% or more compared to traditional stump grinders, without sacrificing the performance that stump grinding professionals need.

The Model 2250XP uses a heavy-duty 40cc hydrostatic motor to directly power its 20" (51cm) diameter cutter wheel. Oversize bearings in the pump handle the shock loads from stump grinding, while an economical 27-horsepower engine powers the hydraulic systems and self-propelled undercarriage. The cutter wheel has a class leading 50" (127cm) swing arc that can also grind to a depth of over 12" (30cm). At just 700kg it's one of the lightest four-wheeled, self-propelled stump grinders available. The travel speed is adjustable so that you can quickly reach the job site, and then be slowed to a crawl-speed while cutting into the stump. With a very tight turning radius and narrow overall machine width your 2250XP will get you into tight access jobs with ease.

Arrange your demo today – you will be amazed at the performance and features of the Bandit 2250XP.

<b>Model</b>	2250XP	<b>Height</b>	48" (120cm)
<b>Self Propelled</b>	2WD standard	<b>Cutter Wheel Drive System</b>	Hydrostatic Drive
<b>Engine Brand</b>	Kohler Command Pro petrol	<b>Cutter Wheel Diameter</b>	20" (50.8cm)
<b>Standard Engine Power</b>	27hp(20kw) 42 ft lbs (57Nm)	<b>Cutter Wheel Width</b>	1" (25.4mm)
<b>Cutting Depth</b>	13" (33cm)	<b>Number of Teeth</b>	18
<b>Cut/Swing Width</b>	50" (127cm)	<b>Tooth Type</b>	Greenteeth
<b>Cutting Height</b>	23" (58cm)	<b>Fuel Tank Capacity</b>	32 litres
<b>Weight</b>	700 kg	<b>Hydraulic Tank Capacity</b>	32 litres
<b>Length</b>	2.7m	<b>Travel Speed</b>	0 - 4.4 kph variable
<b>Width</b>	35.4" (90cm)	<b>Steering</b>	Hydraulic standard

